



# 132-S-900.7<sup>Q&As</sup>

Avaya IP Telephony Design Elective Exam

## Pass Avaya 132-S-900.7 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/132-s-900-7.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

What needs to be considered at an Enterprise Survivability Server (ESS) location when implementing an agent recording solution?

- A. H.323 trunks
- B. locally sourced announcements
- C. Application Enablement Services (AES)
- D. Separation of Bearer and Signaling (SBS)

Correct Answer: C

---

**QUESTION 2**

Which two Avaya servers provide LSP functionality with Communication Manager 5.0? (Choose two.)

- A. S8300
- B. S8400
- C. S8500
- D. S8730

Correct Answer: AC

---

**QUESTION 3**

Which is NOT a service performed by the SIP Enablement Services (SES) Server?

- A. Proxy Server
- B. Location Server
- C. Session Boarder Controller
- D. Registrar

Correct Answer: C

---

**QUESTION 4**

Your client is planning to implement IP Telephony on their recently installed S8500. They will have local IP sets and IP connected remote users (IP Softphone). In addition, they need connectivity to a limited-bandwidth WAN between headquarters and their manufacturing plant. The client is interested in setting up network regions. What are three reasons to consider network regions in your overall design? (Choose three.)



- A. to associate parameters such as codecs and locations to groups of IP endpoints
- B. to provide IP endpoints certain mandatory use of resources that belong in the same region as the endpoint
- C. to provide IP endpoints certain preference to use resources that belong in the same region as the endpoint
- D. to associate IP endpoints with a type of signaling resource (CLANS) to load balance registration among the CLANS in multiple regions
- E. to associate IP endpoints with a type of signaling resource (CLANS) to load balance registration among the CLANS in the same region

Correct Answer: ACE

---

#### QUESTION 5

A major call center outsourcer is in the process of implementing a disaster recovery location and is placing an S8500 Media Server configured as an Enterprise Survivable Server (ESS) at their backup facility. To successfully design a solution that meets the customer needs for survivability and prioritization, what must be done when deploying and administering the ESS servers? (Choose two.)

- A. Avoid overloading the network resources with excessive call traffic
- B. Avoid fragmenting the system so the ESS server controls as much of the network as possible
- C. Ensure that the Manual Backup Server is configured in the priority list of each IP Server Interface (IPSI)
- D. Ensure that every Local Survivable Processor (LSP) is aware of any G650 Media Gateways that will register to it in the event of a network outage

Correct Answer: AB

[132-S-900.7 PDF Dumps](#)

[132-S-900.7 VCE Dumps](#)

[132-S-900.7 Braindumps](#)