



1Y0-440^{Q&As}

Architecting a Citrix Networking Solution

Pass Citrix 1Y0-440 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/1y0-440.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A Citrix Architect has deployed NetScaler Management and Analytics System (NMAS) to monitor a high availability pair of NetScaler VPX devices.

The architect needs to deploy automated configuration backup to meet the following requirements:

1.

The configuration backup file must be protected using a password.

2.

The configuration backup must be performed each day at 8:00 AM GMT.

3.

The configuration backup must also be performed if any changes are made in the ns.conf file.

4.

Once the transfer is successful, auto-delete the configuration file from the NMAS.

Which SNMP trap will trigger the configuration file backup?

A. netScalerConfigSave

B. sysTotSaveConfigs

C. netScalerConfigChange

D. sysconfigSave

Correct Answer: A

Reference: <https://docs.citrix.com/en-us/netscaler-mas/12/instance-management/how-to-backup-andrestore-using-mas.html#configuring-instance-backup-settings>

QUESTION 2

Scenario: More than 10,000 users will access a customer's environment. The current networking infrastructure is capable of supporting the entire workforce of users. However, the number of support staff is limited, and management needs to ensure that they are capable of supporting the full user base.

Which business driver is prioritized, based on the customer's requirements?

A. Simplify Management

B. Increase Scalability

C. Increase Flexibility

D. Reduce Costs



E. Enable Mobile Work Styles

F. Increase Security

Correct Answer: A

QUESTION 3

Scenario: A Citrix Architect needs to plan for a customer environment in which more than 10,000 users will need access. The networking infrastructure needs to be able to handle the expected usage.

Which business driver should be prioritized based on the customer's requirement?

A. Increase flexibility

B. Enable mobile work styles

C. Simplify management

D. Increase Scalability

E. Reduce Costs

F. Increase Security

Correct Answer: D

QUESTION 4

Which two NetScaler cookies indicate the validity of the Authentication, Authorization and Accounting (AAA) session for users? (Choose two.)

A. NSC_WT

B. NSC_TMAS

C. NSC_AAAC

D. NSC_TMAA

Correct Answer: BD

Reference: <https://support.citrix.com/article/CTX202900>

QUESTION 5

Scenario: Based on a discussion between a Citrix Architect and team of Workspacelab has been created across three (3) sites.

They captured the following requirements during the design discussion held for NetScaler design projects:



1.

All three (3) Workspacelab sites (DC, NDR, and DR) will have similar NetScaler configuration and design.

2.

Both external and internal NetScaler MPX appliances will have Global Server Load balancing (GSLB) configured and deployed in Active/Passive mode.

3.

GSLB should resolve both A and AAA DNS queries.

4.

In the GSLB deployment, the NDR site will act as backup for the DC site. whereas the DR site will act as backup for the NDR site.

5.

When the external NetScaler replies to DNS traffic coming in through Cisco Firepower IPS, the replies should be sent back through the same path.

6.

On the internal NetScaler, both front-end VIP and back-end SNIP will be part of the same subnet.

7.

USIP is configured on the DMZ NetScaler appliances.

8.

The external NetScaler will act default gateway for back-end servers.

9.

All three (3) sites (DC, NDR, and DR) will have two (2) links to the Internet from different service providers configured in Active/Standby mode.

Which design decision must the architect make to meet the design requirements above?

A. Interface 0/1 must be used for DNS traffic.

B. The SNIP of the external NetScaler must be configured as default gateway on the back-end servers.

C. ADNS service must be used with IPv6 address.

D. Policy-Based Route with next hop as CISCO IPS must be configured on the external NetScaler.

Correct Answer: C

[Latest 1Y0-440 Dumps](#)

[1Y0-440 VCE Dumps](#)

[1Y0-440 Study Guide](#)