



1Y0-A21^{Q&As}

Basic Administration for Citrix NetScaler 9.2

Pass Citrix 1Y0-A21 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/1y0-a21.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

How can an administrator configure a health check for a server receiving HTTP traffic so that it monitors the response code of the server to actual client requests and NOT to probes whenever possible?

- A. Configure an HTTP-ECV monitor.
- B. Configure an HTTP-Inline monitor.
- C. Use the TCP monitor with the transparent parameter selected.
- D. Configure an HTTP monitor with the transparent parameter selected.

Correct Answer: B

QUESTION 2

Scenario: An administrator plans to configure health checks for services bound to Web servers 1 and 2, which are listening on TCP port 80 for HTTP and TCP port 443 for HTTPS. Service1 receives the clear text traffic and Service2 receives the encrypted traffic.

Which type of monitor should the administrator bind to the services to meet the needs of this environment?

- A. A TCP monitor to Service1 and Service2
- B. An HTTP-ECV monitor to Service1 and Service 2
- C. An HTTPS monitor to Service1 and a HTTP monitor for Service2
- D. An HTTP monitor to Service1 and an HTTPS monitor to Service2

Correct Answer: D

QUESTION 3

An administrator set up a NetScaler pair in HA but later noticed that the configuration changes made on the primary node were NOT synchronized with the secondary node.

Which configuration setting must be corrected for successful configuration synchronization between both nodes in HA mode?

- A. HA monitoring on interfaces is set to off.
- B. HA monitoring on the node IDs is set to off.
- C. nsroot password is not identical for both nodes.
- D. RPC node password is not identical for both nodes.

Correct Answer: D



QUESTION 4

Scenario: An administrator has created a policy expression to identify URLs with the .JSP suffix. The administrator plans to use the policy expression to prevent URLs with the .JSP suffix from being compressed when the HTTP response is received.

How can the administrator associate the policy expression and action to achieve the desired result?

- A. Configure the action, then add a compression policy with the policy expression.
- B. Add a filter with the policy expression and the action specified, then bind the policy.
- C. Configure the action, then add the filter with the policy expression and the action specified.
- D. Add a compression policy with the policy expression and action specified, then bind the policy.

Correct Answer: D

QUESTION 5

An administrator wants to limit access to the NetScaler GUI and has configured ACLs to achieve this; however, everyone is still able to access the NetScaler administration tools.

What could be causing this issue?

- A. Layer-3 mode is enabled.
- B. TCP buffering is enabled.
- C. The configured ACLs have not been applied/committed.
- D. The ACLs have not been propagated to both NetScalers in the HA pair.

Correct Answer: C

[1Y0-A21 PDF Dumps](#)

[1Y0-A21 Study Guide](#)

[1Y0-A21 Exam Questions](#)