1Y0-A28^{Q&As}

Implementing NetScaler 10 for Networking and Traffic Optimization

Pass Citrix 1Y0-A28 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/1Y0-A28.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Citrix Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

Why would an engineer want to specify a TCP Profile for a specific service group?

A. To enable use of features like SSL over TCP for that specific service group.

B. To adjust the TCP settings for traffic to and from that specific service group.

C. To use a specific SNIP for traffic to the back-end servers in that service group.

D. To enable features like use source IP, TCP keep alive and TCP buffering for a specific service group.

Correct Answer: B

QUESTION 2

Scenario: A network engineer is going to roll out an upgrade from a 9.x version on a standalone NetScaler appliance using the command-line interface.

Which two items does the engineer need to download before proceeding with the upgrade? (Choose two.)

A. SSL Certificates Files

B. NetScaler Firmware File

C. NetScaler Configuration file

D. NetScaler Documentation File

Correct Answer: BD

QUESTION 3

Scenario: An engineer has been asked to implement load balancing of an existing unsecured web application. The engineer needs to ensure that users will access the web application using HTTPS, but no changes can be made to the web servers hosting the web application.

In order to fulfill the requirements, the engineer must create an _____ service group and add members with port _____; and bind the service group to an _____ virtual server. (Choose the correct set of options to complete the sentence.)

A. SSL; 443; SSL

B. HTTP; 80; SSL

C. SSL; 80; HTTP

D. HTTPS; 443; HTTP

Correct Answer: B

QUESTION 4

Scenario: A pair of NetScaler devices have recently been installed into the corporate DMZ. The Netscalers have been installed in two-arm mode, with two interfaces in a Internet-facing VLAN and two interfaces in the internal VLAN. A private management subnet also exists.

The NetScaler engineer would like to secure and restrict communication between the management subnet and the SNIP address on that subnet.

Which two actions could the engineer take to help with these goals? (Choose two.)

A. Apply an ACL on the specified SNIP.

B. Remove the ACL list to the internal VLAN.

C. Remove the NSIP address from the Netscaler.

D. Configure the SNIP with the -gui SECUREONLY option.

Correct Answer: AD

QUESTION 5

Scenario: A NetScaler appliance currently has a manually configured channel containing four interfaces; however, the engineer has been told that the NetScaler must now only use a single interface for this network. The engineer removes the channel and immediately notices a decrease in network performance.

How could the engineer resolve this issue?

A. Reset the unused interfaces

B. Disable the unused interfaces

C. Enable flow control on all interfaces

D. Disable HA monitoring on the three interfaces that are no longer required

Correct Answer: B

Latest 1Y0-A28 Dumps   1Y0-A28 PDF Dumps   1Y0-A28 Exam Questions

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

https://www.pass4itsure.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: