



1Z0-811^{Q&As}

Java Foundations

Pass Oracle 1Z0-811 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/1z0-811.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



**QUESTION 1**

Given the code fragment:

```
boolean checkOut = true;
int days = 0;
while (checkOut) {
    days++;
    if (days > 3) {
        checkOut = false;
    }
}
System.out.print(days);
```

What is the result?

- A. 2
- B. 4
- C. The program executes an infinite number of times.
- D. 3

Correct Answer: B

QUESTION 2

You have been asked to develop a Java program that prints the elements of an array in reverse order.

Which looping statement cannot be used to meet the requirement?

- A. enhanced for
- B. standard for
- C. while
- D. do-while

Correct Answer: D

Reference: <https://www.javatpoint.com/java-program-to-print-the-elements-of-an-array-in-reverse-order>

QUESTION 3



```
14 public class Test {  
15     public static void main (String[] args) {  
16         int count = 0;  
17         while (count <= 10) {  
18             System.out.print (count + " ");  
19             count += 2;  
20         }  
21     }  
22 }
```

Execute Mode, Version, Inputs & Arguments

JDK 11.0.4

CommandLine Arguments

Result

CPU Time: 0.20 sec(s), Memory: 33236 kilobyte(s)

0 2 4 6 8 10

Given the code fragment:

```
int[] arr1 = {1, 2, 3};  
int[] arr2 = new int[2];  
arr2[0] = 10;  
System.out.print(arr1.length + " : " + arr2.length);
```

What is the result?

- A. 3 : 1
- B. 3 : 2
- C. 0 : 1
- D. 2 : 0

Correct Answer: B

**QUESTION 4**

Given the contents of the Test.java file:

```
class MyClass {  
    private int var1 = 100;  
    public int var2 = 200;  
    public void doCalc() {  
        var1 = 100 * 2;           // line n1  
        var2 = 200 * 2;  
    }  
}  
  
public class Test {  
    public static void main(String[] args) {  
        MyClass t = new MyClass();  
        t.doCalc();  
        System.out.println (t.var1 + " : " + t.var2);    // line n2  
    }  
}
```

What is the result?

- A. 200 : 400
- B. A compilation error occurs at line n1.
- C. A compilation error occurs at line n2.
- D. 100 : 400

Correct Answer: C

```
15  
16 public class Test {  
17     public static void main(String[] args) {  
18         // MyClass t = new MyClass();  
19  
20         System.out.println(t.var1 + " : " + t.var2);    //Line n2  
21     }  
22 }  
23 }  
24
```

QUESTION 5

Given the code fragment:



```
// line n1  
num = new int[10];
```

Which code fragment can be inserted at line n1 to enable the code to compile?

- A. new int num[];
- B. int[] num;
- C. int[10] num;
- D. int num[10];

Correct Answer: B

[Latest 1Z0-811 Dumps](#)

[1Z0-811 PDF Dumps](#)

[1Z0-811 VCE Dumps](#)