



# 1Z0-816<sup>Q&As</sup>

Java SE 11 Programmer II

**Pass Oracle 1Z0-816 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/1z0-816.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Oracle  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Given:

```
1. public class Secret {
2.     String[] names;
3.     public Secret(String[] names) {
4.         this.names = names;
5.     }
6.     public String[] getNames() {
7.         return names;
8.     }
9. }
```

Which three actions implement Java SE security guidelines? (Choose three.)

- A. Change line 7 to return names.clone();.
- B. Change line 4 to this.names = names.clone();.
- C. Change the getNames() method name to get\$Names().
- D. Change line 6 to public synchronized String[] getNames() {.
- E. Change line 2 to private final String[] names;.
- F. Change line 3 to private Secret(String[] names) {.
- G. Change line 2 to protected volatile String[] names;.

Correct Answer: EFG

---

**QUESTION 2**



```
1 public class Test {
2     private static class Greet {
3         private void print() {
4             System.out.println("Hello World");
5         }
6     }
7     public static void main(String[] args) {
8         Test.Greet i = new Greet();
9         i.print();
10    }
11 }
```

Execute Mode, Version, Inputs & Arguments

JDK 11.0.4

CommandLine Arguments

## Result

CPU Time: 0.16 sec(s), Memory: 32504 kilobyte(s)

Hello World

Assume ds is a DataSource and the EMP table is defined appropriately.

```
try (Connection conn = ds.getConnection();
    PreparedStatement ps = conn.prepareStatement("INSERT INTO EMP VALUES (?, ?, ?)") ) {
    ps.setObject(1, 101, JDBCType.INTEGER);
    ps.setObject(2, "SMITH", JDBCType.VARCHAR);
    ps.setObject(3, "HR", JDBCType.VARCHAR);
    ps.executeUpdate();
    ps.setInt(1, 102);
    ps.setString(2, "JONES");
    ps.executeUpdate();
}
```

What does executing this code fragment do?

- A. inserts two rows (101, 'SMITH', 'HR') and (102, 'JONES', NULL)
- B. inserts two rows (101, 'SMITH', 'HR') and (102, 'JONES', 'HR')
- C. inserts one row (101, 'SMITH', 'HR')
- D. throws a SQLException



Correct Answer: C

---

### QUESTION 3

Given: When run and all three files exist, what is the state of each reader on Line 1?

```
public static void main(String[] args) {
    try (Reader reader1 = new FileReader("File1.txt");
        Reader reader2 = new FileReader("File2.txt");
        Reader reader3 = new FileReader("File3_txt")) {

        } catch (IOException ex) {
            Logger.getLogger(Main.class.getName()).log(Level.SEVERE, null, ex);
        }
    // Line 1
    System.out.println("Done");
}
```

- A. All three readers are still open.
- B. All three readers have been closed.
- C. The compilation fails.
- D. Only reader1 has been closed.

Correct Answer: C

---

### QUESTION 4

Given:



```
public class SerializedMessage implements Serializable {
    String message;
    LocalDateTime createdTime;
    transient LocalDateTime updatedDateTime;;
    SerializedMessage (String message) {
        this.message = message;
        this.createdTime = LocalDateTime.now();
    }
    private void readObject (ObjectInputStream in) {
        try {
            in.defaultReadObject();
            this.updatedDateTime = LocalDateTime.now();
        } catch (IOException | ClassNotFoundException e) {
            e.printStackTrace();
        }
    }
}
```

When is the readObject method called?

- A. before this object is deserialized
- B. after this object is deserialized
- C. before this object is serialized
- D. The method is never called.
- E. after this object is serialized

Correct Answer: B

Reference: <https://www.oracle.com/technical-resources/articles/java/javaserial.html>

---

#### QUESTION 5

Given:

```
enum QUALITY {
    A(100), B(75), C(50);
    int percent;
    private QUALITY(int percent) {
        this.percent = percent;
    }
}
```

and checkQuality(QUALITY.A); and



```
void checkQuality(QUALITY q) {  
    switch (q) {  
        case /* Insert code here */ :  
            System.out.println("Best");  
            break;  
        default :  
            System.out.println("Not best");  
            break;  
    }  
}
```

Which code fragment can be inserted into the switch statement to print Best?

- A. QUALITY.A.ValueOf()
- B. A
- C. A.toString()
- D. QUALITY.A

Correct Answer: B

[1Z0-816 Practice Test](#)

[1Z0-816 Exam Questions](#)

[1Z0-816 Braindumps](#)