



2V0-31.19^{Q&As}

Professional VMware vRealize Automation 7.6

Pass VMware 2V0-31.19 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/2v0-31-19.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A new Windows operating system machine blueprint is created and is ready to be added to a new service catalog.

Which step must be performed for the catalog item to be visible to business users?

- A. Entitle the blueprint with all appropriate actions.
- B. Publish the blueprint.
- C. Entitle a business user to add the blueprint to the catalog.
- D. Add the catalog item to the business group's reservation.

Correct Answer: B

Reference: <https://docs.servicenow.com/bundle/jakarta-it-operations-management/page/product/cloudmanagement-v2/task/catalog-item-from-arm-template.html>

QUESTION 2

What is a specific instance of a completed or running workflow called?

- A. Workflow event
- B. Workflow token
- C. Workflow attribute
- D. Workflow status

Correct Answer: B

Reference: https://docs.vmware.com/en/vRealize-Orchestrator/5.5.1/com.vmware.vsphere.vco_using_client.doc/GUID-9366A590-4DB6-485F-8557-5139EBE12851.html

QUESTION 3

What is prerequisite for creating a NAT or routed network profile in vRealize Automation?

- A. An existing external network profile
- B. A load balancer
- C. A predefined DNS server
- D. A predefined DHCP range

Correct Answer: A

Existing network configured on the vSphere server. They are the external part of the NAT and routed networks types.



An external network profile can define a range of static IP addresses available on the external network. You can use IP ranges obtained from the supplied VMware IPAM endpoint or from a third-party IPAM service provider endpoint that you have registered and configured in vRealize Orchestrator, such as Infoblox IPAM. An IP range is created from an IP block during allocation. An external network profile with a static IP range is a prerequisite for NAT and routed networks.

Reference: <https://docs.vmware.com/en/vRealize-Automation/7.3/com.vmware.vra.prepare.use.doc/GUIDB6E703B8-6F46-4BE0-998D-9B6B7E402129.html>

QUESTION 4

Which two components require a load balancer? (Choose two.)

- A. IaaS Web
- B. IaaS Manager
- C. Proxy Agent
- D. Management Agent
- E. DEM Worker

Correct Answer: AB

Reference: <https://docs.vmware.com/en/vRealize-Automation/7.3/vrealize-automation-load-balancing.pdf>

QUESTION 5

Which three vRealize Automation content types are supported by content lifecycle management in vRealize Suite Lifecycle Manager? (Choose three.)

- A. Resource actions
- B. Endpoints
- C. Reservations
- D. Composite blueprints
- E. Entitlements
- F. Property definitions

Correct Answer: BDF

Reference: <https://docs.vmware.com/en/VMware-vRealize-Suite-Lifecycle-Manager/2018/com.vmware.vrsuite.lcm.20.doc/GUID-CE092BF8-1B49-40EC-B213-CB5D68E46D1E.html>