



2V0-41.20^{Q&As}

Professional VMware NSX-T Data Center

Pass VMware 2V0-41.20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/2v0-41-20.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which three different transport nodes could be configured in the data plane? (Choose three.)

- A. vShield Edge VM
- B. ESXi and KVM
- C. Bare Metal server
- D. NSX Edge VM on KVM
- E. ESXi and Hyper-V
- F. VM or Bare Metal NSX Edge

Correct Answer: BCF

QUESTION 2

Which two BGP configuration parameters can be configured in the VRF Lite gateways? (Choose two.)

- A. Route Aggregation
- B. Route Distribution
- C. Graceful Restart
- D. BGP Neighbors
- E. Local AS

Correct Answer: AD

The following parameters are inherited from the default Tier-0 gateway and cannot be modified at the VRF level:

1.
Local AS
2.
Graceful restart
3.
Graceful restart timer
4.
Graceful restart stale timer
- 5.



Multipath relax

Inter-SR iBGP is not supported in VRF gateways.

BGP can be enabled or disabled per VRF gateway.

Route aggregation and BGP neighbors are local configurations per VRF.

QUESTION 3

When a stateful service is enabled for the first time on a Tier-0 Gateway, what happens on the NSX Edge node?

- A. SR and DR doesn't need to be connected to provide any stateful services.
- B. DR is instantiated and automatically connected with SR.
- C. SR is instantiated and automatically connected with DR.
- D. SR and DR is instantiated but requires manual connection.

Correct Answer: C

QUESTION 4

Where are Distributed Firewall logs containing access decisions stored?

- A. NSX API
- B. NSX Edge
- C. NSX Manager
- D. Hypervisor transport node

Correct Answer: D

<https://docs.vmware.com/en/VMware-NSX-Data-Center-for-vSphere/6.4/com.vmware.nsx.logging.doc/GUID-6F9DC53E-222D-464B-8613-AB2D517CE5E3.html> <https://docs.vmware.com/en/VMware-NSX-T-Data-Center/3.0/administration/GUID-D57429A1-A0A942BE-A299-0C3C3546ABF3.html>

QUESTION 5

Which two statements describe the characteristics of an Edge Cluster in NSX-T 3.0 Data Center? (Choose two.)

- A. can have a maximum of 8 edge nodes
- B. must have only active-active edge nodes
- C. can have a maximum of 10 edge nodes
- D. can contain multiple types of edge nodes (VM or bare metal)



E. must contain only one type of edge nodes (VM or bare metal)

Correct Answer: CD

<https://docs.vmware.com/en/VMware-NSX-T-Data-Center/3.0/installation/GUID-14183A62-8E8D-43CC92E0-E8D72E198D5A.html>

[2V0-41.20 VCE Dumps](#)

[2V0-41.20 Practice Test](#)

[2V0-41.20 Study Guide](#)