300-160^{Q&As}

Designing Cisco Data Center Computing

Pass Cisco 300-160 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/300-160.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

Which access layer technology will provide redundancy if there is a link failure on a server link?

A. VDC

B. MPLS

C. vPC

D. Cisco OTV

Correct Answer: C

QUESTION 2

Which option accurately describes updating vNICs templates?

A. can be used to automate the configuration of STP

B. requires that the same VLANs be enabled on all service profiles and Cisco UCS Fabric Interconnects

C. requires that STP be enabled on all service profiles and Cisco UCS Fabric Interconnects

D. can be used to add or remove VLANs from all of the associated service profiles

Correct Answer: C

QUESTION 3

Which four options about a Cisco Nexus 1000 Series Switch are true? (Choose four.)

A. number of VLANs for Layer 2 connectivity between VSM and VEM: 2

B. VMware vSphere Enterprise Plus Version 4.1 or later; supports VMware vSphere 5.5

C. VMware Distributed Resource Scheduler

D. VMware vShield Zones

E. maximum 1048 active VLANs

F. maximum 2048 port profiles

G. minimum 1048 active VLA

H. minimum 2048 port profiles

Correct Answer: BCDF

QUESTION 4

You have a vPC domain that contains a Cisco Nexus 5000 Series pair. Which feature must you enable to make the Cisco Nexus pair operates as a single STP root?

A. auto-recovery

B. priority

C. peer-switch

D. peer-gateway

Correct Answer: C

QUESTION 5

You are planning to migrate an existing customer infrastructure to a new data center infrastructure. Existing IP addresses must be preserved during the migration. Which three design options must you implement? (Choose three.)

A. Implement a stretched Layer 2 connection that allows for IP mobility.

B. The transport network must provide Layer 3 connectivity between the LISP-enabled routers located in the source and destination data centers.

C. The transport network must provide Layer 2 connectivity between the Cisco FabricPath-enabled routers located in the source and destination data centers.

D. The transport network must provide Layer 3 connectivity between the OTV-enabled routers located in the source and destination data centers.

E. The default gateway in each data center is configured to have the same virtual IP address.

F. The MAC address of the default gateway must be preserved in the new data center.

G. IS-IS must be configured between the data centers to enable Cisco FabricPath functionality.

Correct Answer: ABE

[300-160 PDF Dumps](#)   [300-160 Study Guide](#)   [300-160 Exam Questions](#)

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

https://www.pass4itsure.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: