



# 300-430<sup>Q&As</sup>

Implementing Cisco Enterprise Wireless Networks (ENWLSI)

## Pass Cisco 300-430 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/300-430.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





### QUESTION 1

Refer to the exhibit.

The screenshot shows the configuration page for an Access Control List (ACL) named 'ACL\_Provisioning\_Redirect'. The table below lists the rules in the ACL.

Seq	Action	Source IP/Mask	Destination IP/Mask	Protocol	Source Port	Dest Port
1	Permit	0.0.0.0 / 0.0.0.0	10.230.1.45 / 255.255.255.255	Any	Any	Any
2	Permit	10.230.1.45 / 255.255.255.255	0.0.0.0 / 0.0.0.0	Any	Any	Any
3	Permit	0.0.0.0 / 0.0.0.0	10.225.49.15 / 255.255.255.255	Any	Any	Any
4	Permit	10.225.49.15 / 255.255.255.255	0.0.0.0 / 0.0.0.0	Any	Any	Any
5	Permit	0.0.0.0 / 0.0.0.0	10.230.1.61 / 255.255.255.255	UDP	DHCP Client	DHCP Server
6	Permit	10.230.1.61 / 255.255.255.255	0.0.0.0 / 0.0.0.0	UDP	DHCP Server	DHCP Client
7	Permit	0.0.0.0 / 0.0.0.0	173.194.0.0 / 255.255.0.0	Any	Any	Any
8	Permit	173.194.0.0 / 255.255.0.0	0.0.0.0 / 0.0.0.0	Any	Any	Any
9	Permit	0.0.0.0 / 0.0.0.0	74.125.0.0 / 255.255.0.0	Any	Any	Any
10	Permit	74.125.0.0 / 255.255.0.0	0.0.0.0 / 0.0.0.0	Any	Any	Any
11	Deny	0.0.0.0 / 0.0.0.0	0.0.0.0 / 0.0.0.0	Any	Any	Any

An ACL is configured to restrict access for BYOD clients. The ACL must redirect devices to the guest portal. To which two devices on the local network must the ACL allow access other than the DHCP server? (Choose two.)

- A. SNMP server
- B. Cisco ISE
- C. DNS server
- D. WLCD
- E. RADIUS server

Correct Answer: BC

### QUESTION 2

You are configuring the social login for a guest network. Which three options are configurable social connectors in Cisco CMX Visitor Connect? (Chose three)

- A. Linkedn
- B. Pinterest
- C. Medium
- D. Google+



E. Facebook

F. Myspace

Correct Answer: ADE

---

### QUESTION 3

What is the default NMSP echo interval between Cisco MSE and a Wireless LAN Controller?

A. 10 seconds

B. 15 seconds

C. 30 seconds

D. 60 seconds

Correct Answer: B

Reference:

[https://www.cisco.com/en/US/docs/wireless/mse/3350/6.0/CAS/configuration/guide/msecg\\_ch4\\_CAS.html](https://www.cisco.com/en/US/docs/wireless/mse/3350/6.0/CAS/configuration/guide/msecg_ch4_CAS.html)

---

### QUESTION 4

An engineer configures QoS on an AireOS WLC v8.5. The engineer configures a WLAN for voice traffic and must give a higher priority to WMM clients than to non-WMM clients. Which two configurations should be performed? (Choose two.)

A. Implement the Gold QoS profile.

B. Set Multicast Default Priority to Voice.

C. Set Unicast Default Priority to Platinum.

D. Select Video from the Unicast Default Priority drop-down menu.

E. Implement the Platinum QoS profile.

Correct Answer: CE

---

### QUESTION 5

Refer to the exhibit.



802.11b/g/n Cisco APs >Interference Devices Entries 1 - 2 of 2

Current Filter: None [\[Change Filter\]](#) [\[Clear Filter\]](#)

AP Name	Radio Slot#	Device Type	Affected Channel	Detected Time	Severity	Duty Cycle(%)	RSSI	DevID
RL-C3700-01-HALO	0		1,2,3,4,5,6,7,8,9,11	Mon May 2 14:32:39 2016	63	54	-35	0x3011

An engineer must identify jammer devices on the wireless network. The AP must scan all configured channels. Which AP mode must be configured to accomplish this?

- A. Monitor
- B. Local
- C. FlexConnect
- D. Bridge

Correct Answer: A

[300-430 VCE Dumps](#)

[300-430 Practice Test](#)

[300-430 Exam Questions](#)