



# 300-430<sup>Q&As</sup>

Implementing Cisco Enterprise Wireless Networks (ENWLSI)

## Pass Cisco 300-430 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/300-430.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which QoS level is recommended for guest services?

- A. gold
- B. bronze
- C. platinum
- D. silver

Correct Answer: B

---

**QUESTION 2**

An engineer is configuring the maps on the Cisco Prime Infrastructure, but clients fail to show up on the maps. Which two actions are needed to complete this configuration? (Choose two.)

- A. Install event group services in Cisco Prime Infrastructure.
- B. Synchronize the Cisco WLC with Cisco Prime Infrastructure.
- C. Synchronize the network designs with the Cisco MSE.
- D. Activate the context-aware service on the Cisco MSE.
- E. Install WIPS licenses on the Cisco MSE.

Correct Answer: BC

---

**QUESTION 3**

What is the default NMSP echo interval between Cisco MSE and a Wireless LAN Controller?

- A. 10 seconds
- B. 15 seconds
- C. 30 seconds
- D. 60 seconds

Correct Answer: B

Reference:

[https://www.cisco.com/en/US/docs/wireless/mse/3350/6.0/CAS/configuration/guide/msecg\\_ch4\\_CAS.html](https://www.cisco.com/en/US/docs/wireless/mse/3350/6.0/CAS/configuration/guide/msecg_ch4_CAS.html)

---

**QUESTION 4**

An IT administrator deploys Cisco 2802i APs in all office locations, including main campus and branch offices. The WLC that manages the APs is located at the data center on the main campus. The APs on the main campus are configured to use Local mode and the APs in the branches use FlexConnect mode. Which configuration must be applied to the APs for corporate devices on the main campus to be mapped to the local LAN switch on different VLANs according to the VLAN tag ID and WLAN?

- A. Enable Central DHCP Processing.
- B. Disable FlexConnect Local Auth
- C. Enable FlexConnect Local Switching.
- D. Disable VLAN-based Central Switching.

Correct Answer: A

---

**QUESTION 5**

A new MSE with wIPS service has been installed and no alarm information appears to be reaching the MSE from controllers. Which protocol must be allowed to reach the MSE from the controllers?

- A. SOAP/XML
- B. NMSP
- C. CAPWAP
- D. SNMP

Correct Answer: B

NMSP (Network Mobility Services Protocol) ?The protocol used for communication between Wireless LAN Controllers and the Mobility Services Engine. In the case of a wIPS Deployment, this protocol provides a pathway for alarm information to be aggregated from controllers to the MSE and for wIPS configuration information to be pushed to the controller. This protocol is encrypted.

[https://www.cisco.com/c/en/us/td/docs/wireless/mse/7-6/MSE\\_wIPS/MSE\\_wIPS\\_7\\_6/MSE\\_wIPS\\_7\\_5\\_chapter\\_01000.html](https://www.cisco.com/c/en/us/td/docs/wireless/mse/7-6/MSE_wIPS/MSE_wIPS_7_6/MSE_wIPS_7_5_chapter_01000.html) [https://www.cisco.com/c/en/us/td/docs/wireless/technology/wips/deployment/guide/WiPS\\_deployment\\_guide.html#pgfld-80073](https://www.cisco.com/c/en/us/td/docs/wireless/technology/wips/deployment/guide/WiPS_deployment_guide.html#pgfld-80073)

[Latest 300-430 Dumps](#)

[300-430 PDF Dumps](#)

[300-430 Braindumps](#)