

300-610^{Q&As}

Designing Cisco Data Center Infrastructure (DCID)

Pass Cisco 300-610 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/300-610.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

A network engineer must select a high availability feature for their data center. The solution must ensure network resilience, reduce network instability for Layer 3 routing protocols, and meet these requirements:

1.

The device must notify its neighbors when the control plane is undergoing a restart.

2.

The solution must suppress routing flaps in case of stateful switchovers. Which solution must be implemented?

A. BFD

B. HSRP

C. NSF

D. ISSU

Correct Answer: C

QUESTION 2

An engineer must connect an existing Cisco Fabric Interconnect to an IP-based storage array. The connection be a channel made directly between the fabric interconnect expansion module and the storage array. The engineer must also consider that the environment is running FCoE for storage and uses QoS to prioritize traffic. Which port type should be used to meet these requirements?

A. Network

B. Uplink

C. Appliance

D. server

Correct Answer: B

https://www.cisco.com/c/en/us/support/docs/servers-unified-computing/ucs-5100-series-blade-server-chassis/116075-ucs-app-connectivity-tshoot-00.html

QUESTION 3

An engineer needs an orchestration and monitoring tool that should be used for managing the storage networks and VXLAN fabrics. The tool should also allow support built-in dashboard and real-time health summary for managed devices. Which tool meets these requirements?



- A. Cisco Intersight
- B. Ansible
- C. Puppet
- D. Cisco DCNM
- Correct Answer: D

QUESTION 4

Which two naming formats identify target or initiator iSCSI nodes? (Choose two.)

- A. WWPN
- B. EUI
- C. IQN
- D. WWN
- E. OUI
- Correct Answer: BC

https://docs.vmware.com/en/VMware-vSphere/5.5/com.vmware.vsphere.storage.doc/GUID-686D92B6-A2B2-4944-8718-F1B74F6A2C53.html

QUESTION 5

An engineer must interconnect two geographically separated data centers. The service provide offers a Layer 2 metro Ethernet link. The strict security policy requires that the information that is shared between two sites must be sent encrypted. The application deployed between sites requires a line-rate throughput regardless of the packet size and speed. Which solution meets these requirements?

- A. IPsec
- B. MACsec
- C. L2TPv2
- D. L2TPv3
- Correct Answer: B

https://www.cisco.com/c/dam/en/us/td/docs/solutions/Enterprise/Security/MACsec/WP-High-Speed-WAN-Encrypt-MACsec.pdf



<u>300-610 VCE Dumps</u>

300-610 Study Guide

300-610 Braindumps