



300-625^{Q&As}

Implementing Cisco Storage Area Networking (DCSAN)

Pass Cisco 300-625 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/300-625.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



**QUESTION 1**

A storage administrator manually configures a storage switch to use a new static domain ID. After issuing an `fcdomain restart vsan 1` command, the administrator sees that the switch is still using the existing domain ID. What is the reason why the configuration is not working?

- A. Static domain IDs apply only after a switch is rebooted.
- B. The disruptive keyword was not used on the command.
- C. Build fabric notifications were not sent to the other switches.
- D. Domain manager fast restart is not enabled on the switch.

Correct Answer: A

QUESTION 2

Refer to the exhibit.

```
interface Ethernet 1/10
  priority-flow-control mode auto
```

What is the result of the configuration?

- A. No-drop CoS values are advertised by the DCBX.
- B. LFC is prioritized over PFC on Ethernet 1/10.
- C. PFC operates on Ethernet 1/10 regardless of the capability of the peer.
- D. PFC fails to operate properly unless LFC is disabled on Ethernet 1/10.

Correct Answer: A

QUESTION 3

A Cisco MDS Series Switch with the POAP feature boots and does not find the startup configuration. Which location is checked first when the switch enters POAP mode?

- A. USB device that contains the software image files and the switch configuration file
- B. DHCP server to bootstrap the interface IP address, gateway, DNS server, and TFTP IP addresses
- C. TFTP server where the necessary configuration files are downloaded
- D. HTTP server where the URL is used to download the software image



Correct Answer: A

QUESTION 4

A storage administrator wants to enable NPV in a Fibre Channel edge switch. Which configuration is supported in this mode?

- A. Cisco Fabric Services distribution over Fibre Channel
- B. E Port connectivity to the core switch
- C. local switching of east-west traffic
- D. Dynamic Port VSAN Membership

Correct Answer: A

QUESTION 5

A storage network engineer must install and configure a new MDS switch in a data center network. Which two statements about available choices during the MDS switch initial setup are correct? (Choose two.)

- A. The engineer can choose what will be the administrator account.
- B. The secure password standard is required.
- C. The engineer can configure the default zone policy.
- D. The engineer can configure the default switch port trunk mode.
- E. The engineer does not have the choice to enable or disable full zoneset distribution.

Correct Answer: AC

[300-625 VCE Dumps](#)

[300-625 Practice Test](#)

[300-625 Study Guide](#)