



300-625^{Q&As}

Implementing Cisco Storage Area Networking (DCSAN)

Pass Cisco 300-625 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/300-625.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which result occurs when a VSAN is deleted that contains non-trunking ports?

- A. The ports are moved to VSAN 4094.
- B. The ports are moved to VSAN 1.
- C. The ports are removed from the configuration.
- D. The port configurations are cleared.

Correct Answer: A

QUESTION 2

An engineer is configuring a SAN environment and attempts to activate a zoneset, but a lock is held by another user. Which argument does the engineer use to clear the lock from the zoning database configuration?

- A. commit
- B. abort
- C. clear
- D. force

Correct Answer: C

QUESTION 3

Refer to the exhibit.



```
switch# (config) interface fcip 51
switch# (config) use-profile 10
switch# (config) peer-info ipaddr 10.1.1.1
switch# (config) no shutdown

switch# show fcip profile 10
FCIP Profile 10
Internet Address is 10.0.0.10 (interface GigabitEthernet1/0)
Listen Port is 3225
TCP parameters
SACK is disabled
PMTU discovery is enabled, reset timeout is 3600 sec
Keep alive is 60 sec
Minimum retransmission timeout is 300 ms
Maximum number of re-transmissions is 4
Send buffer size is 0 KB
Maximum allowed bandwidth is 1000000 kbps
Minimum available bandwidth is 15000 kbps
Estimated round trip time is 1000 usec
```

Which configuration change improves the ability of the link to recover from frame loss?

- A. Increase the reset timeout.
- B. Enable selective acknowledgment.
- C. Increase the send buffer size to 15000 KB.
- D. Disable PMTU discovery.

Correct Answer: B

QUESTION 4

Which port mode is used on an NPV device to connect to an NPIV core switch?

- A. E
- B. F
- C. N
- D. NP

Correct Answer: D

QUESTION 5



A Cisco MDS Series Switch with the POAP feature boots and does not find the startup configuration. Which location is checked first when the switch enters POAP mode?

- A. USB device that contains the software image files and the switch configuration file
- B. DHCP server to bootstrap the interface IP address, gateway, DNS server, and TFTP IP addresses
- C. TFTP server where the necessary configuration files are downloaded
- D. HTTP server where the URL is used to download the software image

Correct Answer: A

[Latest 300-625 Dumps](#)

[300-625 Practice Test](#)

[300-625 Study Guide](#)