



# 300-710<sup>Q&As</sup>

Securing Networks with Cisco Firepower (SNCF)

## Pass Cisco 300-710 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/300-710.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





### QUESTION 1

Which command is run at the CLI when logged in to an FTD unit, to determine whether the unit is managed locally or by a remote FMC server?

- A. system generate-troubleshoot
- B. show configuration session
- C. show managers
- D. show running-config | include manager

Correct Answer: C

Reference: [https://www.cisco.com/c/en/us/td/docs/security/firepower/command\\_ref/b\\_Command\\_Reference\\_for\\_Firepower\\_Threat\\_Defense/c\\_3.html](https://www.cisco.com/c/en/us/td/docs/security/firepower/command_ref/b_Command_Reference_for_Firepower_Threat_Defense/c_3.html)

---

### QUESTION 2

Which feature is supported by IRB on Cisco FTD devices?

- A. redundant interface
- B. dynamic routing protocol
- C. EtherChannel interface
- D. high-availability cluster

Correct Answer: A

### QUESTION 3

Which two remediation options are available when Cisco FMC is integrated with Cisco ISE? (Choose two.)

- A. dynamic null route configured
- B. DHCP pool disablement
- C. quarantine
- D. port shutdown
- E. host shutdown

Correct Answer: CD

Reference: <https://www.cisco.com/c/en/us/support/docs/security/identity-services-engine/210524-configure->



firepower-6-1-pxgrid-remediati.html

---

#### QUESTION 4

A security engineer must deploy a Cisco FTD appliance as a bump in the wire to detect intrusion events without disrupting the flow of network traffic. Which two features must be configured to accomplish the task? (Choose two.)

- A. transparent mode
- B. tap mode
- C. bridged mode
- D. inline set pair
- E. passive interfaces

Correct Answer: BD

---

#### QUESTION 5

An administrator is attempting to add a new FTD device to their FMC behind a NAT device with a NAT ID of NAT001 and a password of Cisco0123456789. The private IP address of the FMC server is 192.168.45.45, which is being translated to the public IP address of 209.165.200.225/27. Which command set must be used in order to accomplish this task?

- A. configure manager add 209.165.200.225 255.255.255.224
- B. configure manager add 209.165.200.225
- C. configure manager add 209.165.200.225/27
- D. configure manager add 192.168.45.45

Correct Answer: B

[300-710 PDF Dumps](#)

[300-710 VCE Dumps](#)

[300-710 Braindumps](#)