

300-715^{Q&As}

Implementing and Configuring Cisco Identity Services Engine (SISE)

Pass Cisco 300-715 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/300-715.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

Instant Download After Purchase

- 100% Money Back Guarantee
- 🔅 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

What is the deployment mode when two Cisco ISE nodes are configured in an environment?

- A. distributed
- B. active
- C. standalone
- D. standard

Correct Answer: A

QUESTION 2

Which profiling probe collects the user-agent string?

- A. DHCP
- B. AD
- C. HTTP
- D. NMAP
- Correct Answer: C

QUESTION 3

A company is attempting to improve their BYOD policies and restrict access based on certain criteria

The company\\'s subnets are organized by building. Which attribute should be used in order to gain access based on location?

- A. static group assignment
- B. IP address
- C. device registration status
- D. MAC address

Correct Answer: A

https://www.cisco.com/c/en/us/td/docs/security/ise/2-1/admin_guide/b_ise_admin_guide_21/b_ise_admin_guide_20_ch apter_010100.html#ID1353



QUESTION 4

An organization is implementing Cisco ISE posture services and must ensure that a host-based firewall is in place on every Windows and Mac computer that attempts to access the network They have multiple vendors\\' firewall applications for their devices, so the engineers creating the policies are unable to use a specific application check in order to validate the posture for this

What should be done to enable this type of posture check?

A. Use the file registry condition to ensure that the firewal is installed and running appropriately.

B. Use a compound condition to look for the Windows or Mac native firewall applications.

C. Enable the default firewall condition to check for any vendor firewall application.

D. Enable the default application condition to identify the applications installed and validade the firewall app.

Correct Answer: C

https://www.youtube.com/watch?v=6Kj8P8Hn7dYandt=109sandab_channel=CiscoISE- IdentityServicesEngine

QUESTION 5

An engineer is configuring Cisco ISE policies to support MAB for devices that do not have 802.1X capabilities. The engineer is configuring new endpoint identity groups as conditions to be used in the AuthZ policies, but noticed that the endpoints are not hitting the correct policies.

What must be done in order to get the devices into the right policies?

A. Manually add the MAC addresses of the devices to endpoint ID groups in the context visibility database.

B. Create an AuthZ policy to identify Unknown devices and provide partial network access prior to profiling.

C. Add an identity policy to dynamically add the IP address of the devices to their endpoint identity groups.

D. Identify the non 802.1x supported device types and create custom profiles for them to profile into.

Correct Answer: D

<u>300-715 VCE Dumps</u>

300-715 Study Guide

300-715 Exam Questions