



300-715^{Q&As}

Implementing and Configuring Cisco Identity Services Engine (SISE)

Pass Cisco 300-715 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/300-715.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

Which two features are available when the primary admin node is down and the secondary admin node has not been promoted? (Choose 2)

- A. hotspot
- B. new AD user 802 1X authentication
- C. posture
- D. BYOD
- E. guest AUP

Correct Answer: BC

QUESTION 2

Which port does cisco ISE use for native supplicant provisioning of a windows computer?

- A. TCP/UDP 8905
- B. TCP 8443
- C. TCP/UDP 8909
- D. TCP 443

Correct Answer: A

QUESTION 3

Refer to the exhibit.

```
Switch(config)# gigabitEthernet 1/0/2  
  
Switch(config)# authentication port-control auto  
  
Switch(config)# authentication host-mode multi-auth
```

In which scenario does this switch configuration apply?



- A. when allowing a hub with multiple clients connected
- B. when passing IP phone authentication
- C. when allowing multiple IP phones to be connected
- D. when preventing users with hypervisor

Correct Answer: A

<https://www.linkedin.com/pulse/mac-authentication-bypass-priyanka-kumari#:~:text=Multi%2Dauthentication%20host%20mode%3A%20You,allows%20multiple%20source%20MAC%20addresses.>

QUESTION 4

An administrator connects an HP printer to a dot1x enable port, but the printer is not accessible. Which feature must the administrator enable to access the printer?

- A. MAC authentication bypass
- B. change of authorization
- C. TACACS authentication
- D. RADIUS authentication

Correct Answer: A

<https://community.cisco.com/t5/network-access-control/ise-for-printer-security/m-p/3933216>

QUESTION 5

A user reports that a switch's RADIUS accounting packets are not being seen on the Cisco ISE server. Which command is the user missing in the switch's configuration?

- A. radius-server vsa send accounting
- B. aaa accounting network default start-stop group radius
- C. aaa accounting resource default start-stop group radius
- D. aaa accounting exec default start-stop group radius

Correct Answer: A