



# 300-820<sup>Q&As</sup>

Implementing Cisco Collaboration Cloud and Edge Solutions (CLCEI)

## Pass Cisco 300-820 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/300-820.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A Webex administrator is configuring the Webex Control Hub to enable enterprise users to sign into Webex securely by authenticating to the IdP of the organization. To conform to the SAML specification, to what can the NameID format be set?

- A. urn:oasis:names:tc:SAML:2.0:nameid-format:unspecified
- B. urn:oasis:names:tc:SAML:1.1:nameid-format:emailAddress
- C. urn:oasis:names:tc:SAML:2.0:nameid-format:transient
- D. urn:oasis:names:tc:SAML:1.1:nameid-format:emailAddress

Correct Answer: A

---

**QUESTION 2**

A company is implementing Cisco Webex but has existing legacy Cisco video endpoint registered on-premises. The administrator of Webex wants the SIP address of these rooms to appear in the directory listing on Webex registered endpoints and in the Webex App. How can this be configured?

- A. Using the Directory Connector, room resources without Webex licenses can be synchronized with Webex to make the SIP address appear in the phonebook of the Webex App or the endpoint.
- B. Using the Directory Connector, room resources with flex licenses only can be synchronized with Webex to make the room appear in the phonebook of the Webex App or the endpoint. SIP address is then entered from Control Hub because it will not match the field.
- C. Using the Directory Connector, room resources with flex licenses only can be synchronized with Webex to make the SIP address appear in the phonebook of the Webex App or the endpoint.
- D. Using the Directory Connector, room resources without Webex licenses can be synchronized with Webex to make the room appear in the phonebook of the Webex App or the endpoint. SIP address is then entered from Control Hub because it will not match the field.

Correct Answer: A

---

**QUESTION 3**

A company already has a Cisco Unified Communications Manager for internal audio and video traffic, but it requires video communication with external partners and customers. It is important to ensure security for the deployment and the connectivity.

What must be set up to enable this requirement?

- A. Cisco Unified Border Element and Cisco ASA Firewall
- B. Cisco Unified Border Element and Cisco Firepower Firewall
- C. Cisco Expressway-C and Cisco Expressway-E



D. Cisco Expressway-C and Cisco Unified Border Element

Correct Answer: C

#### QUESTION 4

Refer to the exhibit.

**Create transform** You are here: [Configuration](#) > [Dial plan](#) > [Transform](#) > [Create transform](#)

**Configuration**

Priority	<input type="text" value="5"/>	<a href="#">i</a>
Description	<input type="text" value="Convert Untitled CM supplied domain information to the Expressway SIP domain"/>	<a href="#">i</a>
Pattern type	<input type="text" value="Regex"/>	<a href="#">i</a>
Pattern string	<input type="text" value="(4\d{3})@exp-name.exp.domain*"/>	<a href="#">i</a>
Pattern behavior	<input type="text" value="Replace"/>	<a href="#">i</a>
Replace string	<input type="text" value="\1@exp.domain"/>	<a href="#">i</a>
State	<input type="text" value="Enabled"/>	<a href="#">i</a>

Which description of the transformation is true?

- A. It converts 4123@exp-name.exp.domain: to 4123@exp.domain
- B. It changes all patterns that begin with 4123@exp-name.exp.domain: to 1@exp.domain
- C. It changes 413@exp-name.exp.domain: to 413@exp.domain
- D. It converts 4.3@exp-name.exp.domain: to 1@exp.domain

Correct Answer: A

#### QUESTION 5

A company has a single Expressway-E that exhibits high resource utilization. An engineer checks the logs and finds numerous fraudulent attempts from sip:200@cisco.com. Where must the engineer go to configure a call policy rule and block the desired URI?

- A. Call History Configuration > Call Policy > Rules
- B. Configuration > Call History > Policy > Rules
- C. Configuration > Call Policy > Rules



D. Configuration > Policy > Inbound > Rules

Correct Answer: C

[Latest 300-820 Dumps](#)

[300-820 Practice Test](#)

[300-820 Study Guide](#)