# 312-92<sup>Q&As</sup>

312-92$^{Q\&As}$

## EC-Council Certified Secure Programmer v2

# Pass EC-COUNCIL 312-92 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

**https://www.pass4itsure.com/312-92.html**

**100% Passing Guarantee**
**100% Money Back Assurance**

Following Questions and Answers are all new published by EC-COUNCIL Official Exam Center

**Instant Download** After Purchase

**100% Money Back** Guarantee

**365 Days** Free Update

**800,000+** Satisfied Customers

**QUESTION 1**

William, a software developer just starting his career, was asked to create a website in PHP that would allow visitors to enter a month and a year for their birth date. The PHP code he creates has to validate the input after it is entered. If

William uses the following code, what could a malicious user input to the year value to actually delete the whole website?

$month = $_GET[\\'month\\'];

$year = $_GET[\\'year\\'];

exec("cal $month $year", $result);

print "

" ;

foreach($result as $r)

{

print "$r
";

}

print "

";

A. ";gf -rm *"

B. ";dfr -php *"

C. ";php -rf *"

D. ";rm -rf *"

Correct Answer: D

**QUESTION 2**

Nathan, an application developer, has taken over the lead developer\\'s position and now will administer five other developers. The last lead developer was a programmer specialized in Xcode. Nathan is not familiar with Xcode at all, but will have to learn it to develop programs for company. Nathan come across some code left by the past developer: set this_file to choose file with prompt "Scale your image to 25%" try tell application "Image Capture Scripting" set this_image to open this_file scale this_image by factor 0.35 save this_image in this_file close this_image end tell on error error_message beep buttons {"Process failed")default button1 end try

A. Carbon

B. AppleTalk

C. AppleScript

D. Cocoa

Correct Answer: D

**QUESTION 3**

When the following code is compiled and run is a program what size block will be used to hold name string?

#include

int main(int argc, char **argv)

{

char target[5]="TTTT";

char attacker[11]="AAAAAAAAAA";

strcpy(attacker, " DDDDDDDDDDDDDD");

printf("% \n", target);

return 0;

}

A. 16 bytes

B. 28 bytes

C. 32 bytes

D. 8 bytes

Correct Answer: C

**QUESTION 4**

What type of error will result from the following statement?

int main(int argc, char* argv[])

{

char i[7];

strncpy(i, "sdfusdofof", sizeof(i));

}

A. Unbounded string copy

B. Null-termination

C. String-termination

D. String truncation

Correct Answer: B

---

QUESTION 5

What security package is implemented with the following code?

dwStatus = DsMakSpn

(

"ldap",

"MyServer.Mydomain.com",

NULL,

0,

NULL,

andpcSpnLength,

pszSpn

);

rpcStatus = RpcServerRegisterAuthInfo

(

psz

RPC_C_AUTHN_GSS_NEGOTIATE,

NULL,

NULL

);

A. Diffie-Hellman encryption

B. Repurposing

C. SSPI

D. SMDT

Correct Answer: A