



350-050^{Q&As}

CCIE Wireless Written

Pass Cisco 350-050 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/350-050.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers





Refer to the exhibit.

Looking at the packet capture between the client and AP during a voice troubleshooting session, what can you learn?

- A. The 802.1p COS value is marked as 5, which typically is used for the voice traffic that is encoded in G711.
- B. IP precedence is marked as 5 for the voice traffic that is encoded in G711, with a corresponding 802.11e UP marking of 6.
- C. The WMM UP value is marked as 5, which typically is used for the voice traffic that is encoded in G711, and DSCP is marked as EF.
- D. IP precedence is marked as 5, with a corresponding 802.11e UP marking of 6 and a correct DSCP marking to EF; the voice traffic is encoded in G711.



E. The 802.1p COS value is marked as 5, with a correct DSCP marking to EF, and the voice traffic is encoded in G711.

F. WMM UP marking is marked as 5, which typically is used for video traffic; this voice traffic stream is encoded in G711, and DSCP is marked as EF.

Correct Answer: F

QUESTION 2

Refer to the exhibit.

```
00:1A:E3:5C:B9:A0 MESH_ASSOC_REQUEST_PAYLOAD in Association Request for AP 00:24:F7:BE:18:7F
00:1A:E3:5C:B9:A0 Mesh assoc request for known AP 00:24:f7:be:18:7f
00:1A:E3:5C:B9:A0 Mesh assoc request :child : 00:24:f7:be:18:7f NextHop : 00:00:0c:07:ac:81 LradIp 192.168.130.23
vlanid: 129 mwarPort: 5246 lradPort: 13895
00:1A:E3:5C:B9:A0 Request MAC authorization for AP Child Addr: 00:24:f7:be:18:7f AP Identity: 00:21:a0:d1:c
AWPP Identity: 00:1a:e3:5c:b9:af
MAC Validation of Mesh Assoc Request for 00:24:f7:be:18:7f is -4, Mode is : 0
MAC authoriztion fail. REsetting MSCB state for 00:24:f7:be:18:7f to 9
```



A network administrator is configuring and installing an indoor mesh network using two CAPWAP APs. The APs were out of the box and have already been installed in their designated locations. The RAP is joined to the controller and configured appropriately, but the MAP is not visible on the WLC. In the output shown, which of these explanations is the most likely reason for the issue?

A. The MAP should have been primed to the WLC before being deployed. The Bridge Group Name is not configured by default. The AP policy for the MAP is not configured.

B. The MAP should have been primed to the WLC before being deployed. The Bridge Group Name uses the MAC address and is configured but does not match, which is the reason for the failure.

C. The MAP does not have to be primed to the WLC before being deployed to the field because the WLC discovery process is different for MAPs than it is for RAPs. The Bridge Group Name does not have to match but the RAP has to have the MAP MAC address added to its database.

D. The MAP should have been primed to the WLC before being deployed. The Bridge Group Name does not need to match. The MAP is running an LWAPP image that requires its MAC address to be configured in the RAP in order for a successful join.

E. The MAP does not have to be primed to the WLC before being deployed. The Bridge Group Name needs to match. The AP policy is automatically populated by the MAP discovery process via CAPWAP, but is failing in this example.

Correct Answer: A

QUESTION 3

Company XYZ has a wireless network in place. Which three general guidelines should be followed to overlay a Cisco Context-Aware Mobility Solution? (Choose three.)

A. The maximum effective AP spacing should be between 40 feet and 70 feet.

B. There should be a minimum of two APs within range of each client.



C. APs at the perimeter of the coverage area need to be deployed.

D. The physical placement of APs must be collinear.

E. Equilateral triangle placement of the APs yields better accuracy.

Correct Answer: ACE

QUESTION 4

When using DNS discovery, you must configure DNS to respond to which of the following?

A. CISCO-WAP-CONTROLLER.localdomain

B. CISCO-CONTROLLER.localdomain

C. CISCO-CAPWAP-CONTROLLER.localdomain or CISCO-LWAPP- CONTROLLER.localdomain

D. CISCO-CONTROLLER-LWAPP.localdomain or CISCO-CONTROLLER- CAPWAP.localdomain

Correct Answer: C

QUESTION 5

Refer to the exhibit.

Worst 802.11b/g/n Interferers							
Interferer ID	Type	Status	Affected Channels	Duty Cycle (%)	Discovered	Last Updated	Floor
58:c9:f7:00:00:34	Video Camera	Inactive	6	100	Wed Jul 20 10:08:06 PDT 2011	Wed Jul 20 10:09:28 PDT 2011	System Campus > Demo > First Floor
58:c9:f7:00:00:37	Bluetooth Link	Active	1, 6, 11	1	Thu Jan 01 08:47:33 PST 1970	Wed Jul 20 10:10:42 PDT 2011	System Campus > Demo > First Floor
58:c9:f7:00:00:35	DECT Like Phone	Active	6	20	Wed Jul 20 10:08:35 PDT 2011	Wed Jul 20 10:08:35 PDT 2011	System Campus > Demo > First Floor
58:c9:f7:00:00:36	DECT Phone	Active	6, 11	43	Wed Jul 20 10:08:43 PDT 2011	Wed Jul 20 10:10:24 PDT 2011	System Campus > Demo > First Floor

According to the Cisco WCS CleanAir dashboard, which interferer is causing the most interference at the time of the capture?

A. video camera



- B. Bluetooth link
- C. DECT-like phone
- D. DECT phone

Correct Answer: D

[350-050 PDF Dumps](#)

[350-050 Practice Test](#)

[350-050 Exam Questions](#)



To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

<https://www.pass4itsure.com/allproducts>

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 One Year Free Update <p>Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 Money Back Guarantee <p>To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 Security & Privacy <p>We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4itsure, All Rights Reserved.