



3605^{Q&As}

Avaya Ethernet Routing Switch Implementation and Maintenance Exam

Pass Avaya 3605 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/3605.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

A customer needs to install a new Ethernet Routing Switch (ERS) 2550T on the 172.16.5.0/24 network, but does not have a console cable available. Which statement is correct?

- A. The switch will first attempt to use BootP to acquire an IP address, and if that fails it will assign IP address 192.160.1.1/24 to the switch IP.
- B. The customer can set the switch to use the temporary address of 192.168.192.168 by pressing the User Interface button on the front of the ERS 2550T
- C. To communicate with an ERS 2550T the IP address must first be set though the console interface.
- D. The customer can connect to the network management Ethernet port which is pre-configured to use the 192 168 1 1/24 IP address

Correct Answer: D

QUESTION 2

Refer to the exhibit.



When checking an Inter Switch Trunks (IST) configuration using the show mlt ist info command as shown in the exhibit, which IP address should be in the IP ADDRESS column?

- A. The IP address of the IST VLAN on the local switch.
- B. The IP address of the IST VLAN on the peer switch.
- C. The IP address of the first IST port on the peer switch.
- D. The management IP address of the peer switch.

Correct Answer: B

QUESTION 3

When multiple VLANs are used, Dynamic Host Control Protocol (DHCP) relay is required to get the DHCP information



from the end user VLAN DHCP server. Which statement about how to enable DHCP relay is true?

- A. The physical VLAN IP address is configured as the DHCP relay agent on each VLAN requiring a DHCP relay.
- B. The IP address of the DHCP server is configured as the relay agent globally on all switches that do not directly attach to the DHCP server.
- C. The MAC address of the DHCP server configured as the DHCP relay agent on each VLAN requiring the DHCP relay agent.
- D. The DHCP relay is configured globally and is automatically applied to all VLANs requiring a DHCP relay.

Correct Answer: A

QUESTION 4

During a power-on or cold-start sequence, at which stage can the flags to change the operational environment of the switch be set?

- A. boot monitor prompt
- B. image search
- C. PC system test
- D. boot configuration prompt

Correct Answer: A

QUESTION 5

A technician is configuring the core of a Converged Campus network, and is adding a backup-master configuration to an existing Virtual Router Redundancy Protocol (VRRP) configuration for a VLAN that extends to the edge switches. Which benefit is expected from the addition of backup-master?

- A. reduced traffic on the Inter Switch Trunks (IST)
- B. reduced traffic on the uplink ports
- C. redundant default gateways for host devices
- D. reduces VRRP hello packets

Correct Answer: A

[Latest 3605 Dumps](#)

[3605 PDF Dumps](#)

[3605 Braindumps](#)