

400-351^{Q&As}

CCIE Wireless Written

Pass Cisco 400-351 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass4itsure.com/400-351.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





https://www.pass4itsure.com/400-351.html

2022 Latest pass4itsure 400-351 PDF and VCE dumps Download

QUESTION 1

A wireless engineer must configure bandwidth-based admission control on the company WLC for video applications. After applying the necessary configuration changes to the corporate WLAN, the engineer notices that the bandwidth is not

being allocated correctly.

Which problem is true?

- A. Admission control cannot work with 802.1X security.
- B. The WLAN must have gold QoS configured.
- C. Only CCX v2 clients were connected to the WLAN at the time of the testing.
- D. An AVC profile must be assigned to the WLAN for the admission control to work properly.

Correct Answer: B

QUESTION 2

You have been hired to install new Cisco switches at ACME Corporation. The company has an existing Cisco network comprised of access layer switches that use multiple VLANs and VLAN trunking protocol to distribute the VLANs to the switches throughout the network. Which two methods are best to accomplish your task? (Choose two.)

- A. Configure the VLAN Trunking Protocol pruning on the new switches because they may not need all of the VLANs.
- B. Prior to installation, ensure that all switches are running the same Cisco IOS software version as the VTP server.
- C. Ensure that all the new Cisco switches have their VTP domain name set to the default value of null
- D. Configure one of the new switches as a VTP server to distribute the VLANs appropriately.
- E. Ensure that all switches have the same VLAN Trunking Protocol password and encryption level.
- F. Configure all new switches as VTP clients and relocated switches as VTP server because the already have all the VLANs in their database.
- G. Ensure that all switches are running the same VTP version.

Correct Answer: EG

From:



https://www.pass4itsure.com/400-351.html

2022 Latest pass4itsure 400-351 PDF and VCE dumps Download

VTP Configuration Guidelines and Restrictions

Follow these guidelines and restrictions when implementing VTP in your network

- All network devices in a VTP domain must run the same VTP version.
- You must configure a password on each network device in the management domain when VTP is in secure mode.



Caution If you configure VTP in secure mode, the management domain will not function properly if you do not assign a management domain password to each network device in the domain.

http://www.cisco.com/c/en/us/td/docs/switches/lan/catalyst4500/12-2/25ew/configuration/guide/conf/vtp.html#wp1034490

QUESTION 3

When configuring Application Visibility and Control on the wireless controller, which two restrictions must be considered prior to AVC configuration and implementation? (Choose two.)

- A. IPv6 packet classification is not supported.
- B. The number of applications that you can apply rate limit is 9.
- C. Controller CLI support is not present for the AVC Protocol Pack feature.
- D. AVC rate limiting is not supported on the Cisco 5520 WLCs.
- E. Multicast traffic is not supported.

Correct Answer: AC

QUESTION 4

Which three statements about the high availability configuration on the Cisco 5760 WLCs are true? (Choose three.)

- A. Cisco WLC with more reboots is elected as active when the default stack priority is in use.
- B. EtherChannel bundles all ports on both active and standby Cisco WLC on a logical port.
- C. Cisco 5760 WLC uses a dedicated high availability port for high availability and configuration synchronization.
- D. High availability switchover is triggered when one of the ports on the active Cisco WLC EtherChannel bundle fails.
- E. Active Cisco WLCs in a pair can be identified using LED state without issuing any command on the Cisco WLC console.
- F. Cisco WLC with the highest priority in a stack are elected as the active Cisco WLC during the election process.
- G. All configuration including certificates are automatically synced between active and standby Cisco WLC.

Correct Answer: BEF

 $http://www.cisco.com/c/en/us/td/docs/wireless/technology/5760_deploy/CT5760_Controller_Deployment_Guide/High_Availability.html$



https://www.pass4itsure.com/400-351.html 2022 Latest pass4itsure 400-351 PDF and VCE dumps Download

QUESTION 5

Which two characteristics of an IoT network are true? (Choose two.)

- A. The transmission rate in an IoT network is consistent.
- B. loT networks must be designed for low-powered devices.
- C. loT networks use IS-IS for routing.
- D. loT networks are 100% reliable
- E. IoT networks are bandwidth constrained

Correct Answer: BE

400-351 VCE Dumps

400-351 Practice Test

400-351 Study Guide



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.pass4itsure.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited. All trademarks are the property of their respective owners. Copyright © pass4itsure, All Rights Reserved.