4A0-104^{Q&As}

Alcatel-Lucent Services Architecture

Pass Alcatel-Lucent 4A0-104 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/4a0-104.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Alcatel-Lucent Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

365 Days Free Update

800,000+ Satisfied Customers

QUESTION 1

How many SAPs can be configured on a port configured with dot1q encapsulation?

A. 1

B. 4095

C. None. This encapsulation is not supported.

D. The number is limited only by the capacity of the router

Correct Answer: B

QUESTION 2

On a Nokia 7750 SR, why must the MTU be explicitly set when configuring an IES spoke termination to a VPLS?

A. By default, a VPLS signals an MTU based on the network port.

B. By default, an IES sets its ip-mtu to the VC MTU of the VPLS.

C. By default, an IES uses an MTU value based on its SAP.

D. By default, an IES uses an MTU based on the network port.

Correct Answer: D

QUESTION 3

In a Layer 2 encapsulation using T-LDP, what does the first (top) label represent?

A. Tunnel Label

B. VC Label

C. Operational Control Word

D. UNI

E. NNI

Correct Answer: A

QUESTION 4

In a Layer 2 VPN service, the FCS is stripped when a customer packet arrives at the ingress PE and regenerated on egress.

A. TRUE

B. FALSE

Correct Answer: A

QUESTION 5

Which of the following SAPs will forward tagged frames with an outer VLAN tag of 200? (Choose three.)

A. sap 1/1/1

B. sap 1/1/1:*

C. sap 1/1/1:*.0

D. sap 1/1/1:0*

E. sap 1/1/1:200.*

F. sap 1/1/1:300:200

Correct Answer: ABE