



4A0-M10^{Q&As}

Nokia 5G Packet Core Architecture

Pass Nokia 4A0-M10 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/4a0-m10.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

Which of the following statements about the downlink user plane data flow in Option 3X is FALSE?

- A. Data packets of bearers that do not use dual connectivity are sent from EPC to UE through eNB.
- B. When NR coverage is good, data packets of bearers that use dual connectivity are sent from EPC to UE using secondary cell group bearers.
- C. When NR coverage degrades, the gNB decides when to use split bearers and send some of the packets received from the core through eNB.
- D. When NR coverage is poor, data packets of bearers that use dual connectivity are sent to the UE through eNB.

Correct Answer: D

QUESTION 2

Which Nokia product is used for the AMF in 5GS?

- A. Cloud Mobility Manager
- B. Cloud Mobile Gateway
- C. Network Resource Discovery
- D. Smart Plan Suite

Correct Answer: A

Reference: <https://www.nokia.com/networks/products/cloud-mobility-manager/>

QUESTION 3

The exhibit below displays a packet capture of the PFCP Session Modification Request message sent during a PDU Session Establishments procedure. What do the highlighted TEID and IP Address refer to?



Source	Destination	Protocol	Length	Info
SMF	UPF	PFCP	198	PFCP Session Modification Request
Message Type: PFCP Session Modification Request (52)				
Length: 152				
SEID: 0x000000000001a100				
Sequence Number: 786434				
Spare: 0				
▼ Update FAR : [Grouped IE]				
IE Type: Update FAR (10)				
IE Length: 62				
> FAR ID: Dynamic by CP 537198592				
▼ Apply Action:				
IE Type: Apply Action (44)				
IE Length: 1				
> Flags: 0x02, FORM (Forward)				
▼ Update Forwarding Parameters : [Grouped IE]				
IE Type: Update Forwarding Parameters (11)				
IE Length: 45				
> Destination Interface : Access				
> Network Instance : n3-default				
▼ Outer Header Creation :				
IE Type: Outer Header Creation (84)				
IE Length: 10				
Outer Header Creation Description: GTP-U/UDP/IPv4 (256)				
TEID: 0x10000001				
IPv4 Address: 10.10.100.32 (10.10.100.32)				

- A. The N3 TEID allocated by gNB and the gNB IP address.
- B. The N3 TEID allocated by UPF and the UPF IP address.
- C. The N3 TEID allocated by SMF and the SMF IP address.
- D. The N3 TEID allocated by SMF and the UPF IP address.

Correct Answer: D

QUESTION 4

Which of the following is an HTTP method used by an NF service consumer to create a new resource at an NF service producer when the resource URI is selected by the consumer?

- A. POST
- B. PUT



C. PATCH

D. UPDATE

Correct Answer: B

Reference: https://www.tech-invite.com/3m29/toc/tinv-3gpp-29-501_c.html

QUESTION 5

Which of the following statements regarding cloud RAN architecture is FALSE?

A. The gNB is split into three functional modules: a radio unit (RU), a distributed unit (DU), and a centralized unit (CU).

B. DU performs the non-real time processing of layer 2.

C. The fronthaul segment connects RU to DU and the midhaul segment connects DU to CU.

D. CU can be deployed in the cloud as a VNF.

Correct Answer: D

Reference: <https://www.5gtechnologyworld.com/open-ran-functional-splits-explained/>

[4A0-M10 PDF Dumps](#)

[4A0-M10 VCE Dumps](#)

[4A0-M10 Study Guide](#)