



4A0-M10^{Q&As}

Nokia 5G Packet Core Architecture

Pass Nokia 4A0-M10 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/4a0-m10.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Nokia
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Which of the following actions is NOT performed during an Xn-based Inter NG-RAN Handover with I-UPF Insertion procedure?

- A. AMF determines that a new I-UPF needs to be added for a PDU session.
- B. SMF provides N3 tunnel info of I-UPF to target gNB via AMF.
- C. SMF provides N9 tunnel info of UPF PSA to I-UPF.
- D. SMF provides N9 tunnel info of I-UPF to UPF PSA.

Correct Answer: B

QUESTION 2

Which of the following statements about 5GS PDU sessions is FALSE?

- A. A PDU session allows for the exchange of PDUs between UE and a data network.
- B. A PDU session contains one single dedicated radio bearer and one or more N3 GTP-U tunnels.
- C. A PDU session has one default QoS flow and can have multiple non-default QoS flows.
- D. A PDU session has one or more UPFs acting as PDU session anchors.

Correct Answer: B

QUESTION 3

Which of the following statements about the protection of service-based interfaces (SBIs) is FALSE?

- A. The transport layer security (TLS) performs certification-based authentication, providing connection security between network functions within a PLMN.
- B. The OAuth 2.0 framework is used to secure the communication between network functions within a PLMN at the network layer.
- C. The network domain security/Internet protocol (NDS/IP) provides confidentiality and data integrity between network functions within a PLMN.
- D. The security edge protection proxy (SEPP) handles the security of inter-domain SBIs and protects the interaction between network functions in different PLMNs.

Correct Answer: D



Reference: <https://www.broadforward.com/security-edge-protection-proxy/>

QUESTION 4

Which of the following actions is NOT performed when handling an uplink data packet?

- A. UE maps the uplink data packet to a QoS Flow based on QoS rules received from SMF.
- B. UE maps the QoS Flow identifier to a data radio bearer based on QFI-to-DRB mapping received from NG-RAN.
- C. NG-RAN marks the data packet with the proper DSCP value.
- D. NG-RAN removes the QoS Flow identifier from the packet header and forwards the packet over the proper N3 GTP-U tunnel.

Correct Answer: A

QUESTION 5

When an idle UE moves from EPS to 5GS, which procedure is performed?

- A. Registration
- B. Tracking Area Update
- C. Initial Attach
- D. Service Request

Correct Answer: C

Reference: <https://itectec.com/spec/5-17-interworking-and-migration/>

[4A0-M10 PDF Dumps](#)

[4A0-M10 Exam Questions](#)

[4A0-M10 Braindumps](#)