

# 4A0-M10<sup>Q&As</sup>

Nokia 5G Packet Core Architecture

## Pass Nokia 4A0-M10 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass4itsure.com/4a0-m10.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Nokia
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



### https://www.pass4itsure.com/4a0-m10.html

2024 Latest pass4itsure 4A0-M10 PDF and VCE dumps Download

#### **QUESTION 1**

Which of the following statements regarding the 5G security components is FALSE?

- A. The authentication credential repository and processing function (ARPF) selects the authentication method to use for the UE.
- B. The authentication server function (AUSF) handles authentication requests for both 3GPP and non3GPP access.
- C. The security anchor function (SEAF) makes the final decision on UE authentication.
- D. The security identifier de-concealing function (SIDF) decrypts the UE\\'s SUCI to obtain its corresponding SUPI.

Correct Answer: D

Reference: https://www.etsi.org/deliver/etsi\_ts/133500\_133599/133501/15.02.00\_60/ts\_133501v150200p.pdf

#### **QUESTION 2**

Which of the following statements about the downlink user plane data flow in Option 3X is FALSE?

- A. Data packets of bearers that do not use dual connectivity are sent from EPC to UE through eNB.
- B. When NR coverage is good, data packets of bearers that use dual connectivity are sent from EPC to UE using secondary cell group bearers.
- C. When NR coverage degrades, the gNB decides when to use split bearers and send some of the packets received from the core through eNB.
- D. When NR coverage is poor, data packets of bearers that use dual connectivity are sent to the UE through eNB.

Correct Answer: D

#### **QUESTION 3**

The exhibit below displays a packet capture of the PFCP Session Modification Request message sent during a PDU Session Establishments procedure. What do the highlighted TEID and IP Address refer to?

#### https://www.pass4itsure.com/4a0-m10.html

2024 Latest pass4itsure 4A0-M10 PDF and VCE dumps Download

```
Source
          Destination
                         Protocol
                                     Length Info
                                             PFCP Session Modification Request
SMF
            UPF
                          PFCP
                                     198
  Message Type: PFCP Session Modification Request (52)
  Length: 152
  SEID: 0x000000000001a100
  Sequence Number: 786434
  Spare: 0

▼ Update FAR : [Grouped IE]

     IE Type: Update FAR (10)
     IE Length: 62
   > FAR ID: Dynamic by CP 537198592

→ Apply Action:
        IE Type: Apply Action (44)
        IE Length: 1
      > Flags: 0x02, FORM (Forward)
   IE Type: Update Forwarding Parameters (11)
        IE Length: 45
      > Destination Interface : Access
     > Network Instance : n3-default

→ Outer Header Creation :
          IE Type: Outer Header Creation (84)
          IE Length: 10
          Outer Header Creation Description: GTP-U/UDP/IPv4 (256)
          TEID: 0x10000001
          IPv4 Address: 10.10.100.32 (10.10.100.32)
```

- A. The N3 TEID allocated by gNB and the gNB IP address.
- B. The N3 TEID allocated by UPF and the UPF IP address.
- C. The N3 TEID allocated by SMF and the SMF IP address.
- D. The N3 TEID allocated by SMF and the UPF IP address.

Correct Answer: D

#### **QUESTION 4**

Which of the following statements about the protection of service-based interfaces (SBIs) is FALSE?

- A. The transport layer security (TLS) performs certification-based authentication, providing connection security between network functions within a PLMN.
- B. The OAuth 2.0 framework is used to secure the communication between network functions within a PLMN at the



## https://www.pass4itsure.com/4a0-m10.html

2024 Latest pass4itsure 4A0-M10 PDF and VCE dumps Download

network layer.

- C. The network domain security/Internet protocol (NDS/IP) provides confidentiality and data integrity between network functions within a PLMN.
- D. The security edge protection proxy (SEPP) handles the security of inter-domain SBIs and protects the interaction between network functions in different PLMNs.

Correct Answer: D

Reference: https://www.broadforward.com/security-edge-protection-proxy/

#### **QUESTION 5**

NF A wants to explicitly subscribe for event notifications at NF B. Which of the following actions regarding this mechanism is FALSE?

- A. NF A acts as a service consumer and NF B acts as a service producer.
- B. NF A includes a subscription identifier in the request message sent to NF B.
- C. NF A includes a callback URI in the request message sent to NF B.
- D. NF A includes event filtering criteria in the request message sent to NF B.

Correct Answer: C

4A0-M10 PDF Dumps

4A0-M10 VCE Dumps

4A0-M10 Practice Test