

## 500-601<sup>Q&As</sup>

Application Centric Infrastructure Support Representative

## Pass Cisco 500-601 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass4itsure.com/500-601.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



## https://www.pass4itsure.com/500-601.html

2024 Latest pass4itsure 500-601 PDF and VCE dumps Download

### **QUESTION 1**

Which two statements about Cisco ACI interaction with STP in legacy networks are true? (Choose two)

- A. External switches ignore flooded BPDU frames received from the Cisco ACI fabric.
- B. BPDU guard is enabled on FEX ports by default.
- C. BPDU guard cannot be configured on leaf edge ports.
- D. STP is enabled by default within the Cisco ACI fabric.
- E. BPDU frame is flooded within EPG No configuration is required.

Correct Answer: AD

#### **QUESTION 2**

Which two statements about tenant bridge domain Layer 2 unknown unicast forwarding modes are true\\'? (Choose two.)

- A. If forwarding mode is flood, unknown Layer 2 unicast is sent to all Layer 2 ports in the bridge domain.
- B. If forwarding mode is proxy, unknown Layer 2 unicast packets are sent to border leaf proxy for forwarding.
- C. By default, multicast traffic is always flooded within the bridge domain VLAN.
- D. Layer 2 unknown unicast can be set to flood or proxy, the default is flood.
- E. If border leaf proxy cannot resolve the destination, packet is flooded.

Correct Answer: AB

#### **QUESTION 3**

When you use a Cisco UCS fabric interconnect, which protocol must be configured between the fabric interconnect and the ESX/ server?

- A. PFC
- B. vPC
- C. HSRP
- D. Cisco Discovery Protocol

Correct Answer: B

## QUESTION 4

# VCE & PDF Pass4itSure.com

## https://www.pass4itsure.com/500-601.html

2024 Latest pass4itsure 500-601 PDF and VCE dumps Download

Refer to the exhibit The configured bridge domain with name "Prod-BD" m tenant Prod is not functioning property Which option describes a possible reason for that failure?

# fv . RsCtx

childAction :

Dn : uni/tn-Prod/BD-Prod-BD/rsctx

forceResolve : yes lcOwn : local

modTs : 2015-06-12T15:03:08.016+01:00 monPolDn : uni/tn-common/monepg-default

rType : mo

Rn : rsctx

State : missing-target

stateQual : none

Status :

tCl : fvCtx

tContextDn :

tDn :

tRn : ctx-Prod-vrf

tType : name

tnFvCtxName : prod-vrf

uid : 0

- A. The context "Prod-vrf" does not exist m the fabric.
- B. The "missing-target" state field indicates that there are not leaves with endpoint in the bridge domain, so it is not configured anywhere.
- C. Someone has deleted the monitoring object "monepg default".
- D. The tenant "Prod" has been deleted.

Correct Answer: A

### **QUESTION 5**

Which two statements are true regarding ARP request/response on an ACI Fabric? (Choose two.)

- A. ARP requests come in on the elected/designated FD encapsulation VLAN under the BD.
- B. ARP request can be captured using icpdump" on spine switches.



## https://www.pass4itsure.com/500-601.html

2024 Latest pass4itsure 500-601 PDF and VCE dumps Download

- C. ARP traffic is handled by the broadcom ASIC it the two endpoints are in the same EPG and the same FD VLAN.
- D. ARP requests are sent to CPU only if they are for the Bridge Domain SVI IP address
- E. ELAM can be used to capture ARP request/response frames in the Leaf front panel Broadcom ASIC.

Correct Answer: DE

500-601 PDF Dumps

500-601 VCE Dumps

500-601 Practice Test