



# 500-920<sup>Q&As</sup>

Cisco Data Center Unified Computing Infrastructure Troubleshooting  
(DCITUC)

## Pass Cisco 500-920 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/500-920.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

You are in the process of upgrading your UCS M3 Server to a newer UCS M4 Server. You associate the Service Profile to the new UCS Server, but it fails to boot. You suspect of a failed boot hard drive. You check your RAID1 Boot LUN in UCS Manager, but see no error messages.

What could be causing the issue?

- A. The newer Cisco UCS M4 Server is using flash drives, not hard drives
- B. The newer Cisco UCS M4 Server is using disks of larger capacity than the previous UCS M3 Server
- C. A misconfiguration on the Service Profile Local Boot Policy
- D. A misconfiguration on the Service Profile Local Disk Policy

Correct Answer: A

---

**QUESTION 2**

When it comes to pinning vNIC traffic from a UCS Server to the Fabric Interconnect uplink, what configuration can you perform?

- A. You can configure Automatic Uplink Pinning. If an uplink interface fails on one Fabric Interconnect, the server will fail to the first available uplink on the other Fabric Interconnect
- B. You can configure Static Uplink Pinning. If an uplink interface fails on one Fabric Interconnect, the server will fail to the first available uplink on the other Fabric Interconnect
- C. You can configure Automatic Uplink Pinning. If an uplink interface fails on one Fabric Interconnect, the server will fail to the matching uplink on the other Fabric Interconnect
- D. You can configure Static Uplink Pinning. If an uplink interface fails on one Fabric Interconnect, the server will fail to the first available uplink on the same Fabric Interconnect
- E. You can configure Static Uplink Pinning. If an uplink interface fails on one Fabric Interconnect, the server will fail to the matching uplink on the other Fabric Interconnect

Correct Answer: A

---

**QUESTION 3**

After installing a new UCS M4 server, which two Cisco Integrated Management Controller connectivity options do you have? (Choose two)

- A. XML API Access
- B. Web Access



- C. In-band Access
- D. SNMP
- E. Out-of-Band Access

Correct Answer: AC

---

#### QUESTION 4

When booting up a Cisco UCS Server you want to see boot time diagnostic messages of the POST, what action is required for you to do so?

- A. Enable Quiet Boot on the Server\\'s BIOS
- B. Restart the Server
- C. Disable Fast Boot on the Server\\'s BIOS
- D. Enable Quiet Boot on the Server\\'s Service Profile
- E. Disable Fast Boot on the Server\\'s Service Profile

Correct Answer: D

---

#### QUESTION 5

After performing a UCS firmware upgrade, which two UCS components will require updated drivers? (Choose two )

- A. VIC Cards and Fiber Channel HBAs
- B. Cisco Fabric Interconnects
- C. Cisco UCS Manager
- D. RAID Controllers

Correct Answer: AB

[Latest 500-920 Dumps](#)

[500-920 Practice Test](#)

[500-920 Exam Questions](#)