



500-920^{Q&As}

Cisco Data Center Unified Computing Infrastructure Troubleshooting
(DCITUC)

Pass Cisco 500-920 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/500-920.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which two formats can be configured for Cisco's Call Home email message? (Choose two)

- A. JSON
- B. CSV
- C. Full text
- D. XML

Correct Answer: CD

<http://www.audentia-gestion.fr/cisco/smart-call-home-feature-guide-1611.pdf>

Call Home Message Formats The Call Home feature offers the following message formats:

Short Text -- Suitable for pagers or printed reports.

Plain Text -- Full formatted message information suitable for human reading.

XML -- Matching readable format using Extensible Markup Language (XML) and Adaptive Markup Language (AML) document type definitions (DTDs).

The XML format enables communication with the Cisco TAC. For user- defined destination profiles, the format options are long-text, short-text, or XML. The default is XML. For the predefined Cisco TAC profile, only XML is allowed.

QUESTION 2

When booting up a Cisco UCS Server you want to see boot time diagnostic messages of the POST, what action is required for you to do so?

- A. Enable Quiet Boot on the Server's BIOS
- B. Restart the Server
- C. Disable Fast Boot on the Server's BIOS
- D. Enable Quiet Boot on the Server's Service Profile
- E. Disable Fast Boot on the Server's Service Profile

Correct Answer: D

QUESTION 3



When troubleshooting a LAN connectivity issue, you notice a failed uplink from the Cisco UCS Fabric Interconnects to the upstream LAN switch. What two could be causing the issue? (Choose two)

- A. Misconfigured VLAN on the failed uplink
- B. Misconfigured QoS parameters on the failed uplink
- C. A port channel mismatch between the Fabric Interconnects and the upstream LAN switch
- D. A SFP Type mismatch between the Fabric Interconnects and the upstream LAN switch
- E. A port speed configuration mismatch between the Fabric Interconnects and the upstream LAN switch

Correct Answer: BC

QUESTION 4

Which statement is true regarding the UCS Manager GUI is showing "Overall Status Unassociated" in the General tab for a C-series server?

- A. The server has a service profile assigned, but has connectivity issues with UCS Manager
- B. The server is not properly connected
- C. The server does not have a service profile assigned, but has been discovered by UCS Manager
- D. The server has been properly connected, but has not been discovered by UCS Manager

Correct Answer: B

QUESTION 5

In order to create an Inband Profile for Cisco Integrated Management Controller (IMC) connectivity, what do you need to perform first?

- A. Create a Management IP Pool, a MAC Address Pool, and a VLAN Pool
- B. Create an IPMI Policy
- C. Create a Service Profile
- D. Create different VLANs, with different VLAN IDs
- E. Create a Management IP Pool, a VLAN, and a VLAN Group

Correct Answer: C