



5V0-21.19^{Q&As}

VMware vSAN 6.7 Specialist Exam 2019

Pass VMware 5V0-21.19 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/5v0-21-19.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

- ⚙ **Instant Download** After Purchase
- ⚙ **100% Money Back** Guarantee
- ⚙ **365 Days** Free Update
- ⚙ **800,000+** Satisfied Customers



**QUESTION 1**

Refer to the exhibit.

Availability	Advanced Policy Rules	Tags
Site disaster tolerance ⓘ		Dual site mirroring (stretched cluster) ▼
Failures to tolerate ⓘ		1 failure - RAID-5 (Erasure Coding) ▼

What is the minimum number of data nodes across all sites in a vSAN stretched cluster configuration with the above storage policy?

- A. 4
- B. 6
- C. 8
- D. 9

Correct Answer: B

QUESTION 2

A 3-node vSAN cluster will take which two actions, when a drive is physically removed from a vSAN node? (Choose two.)

- A. Marks all components on that device as absent
- B. Marks all components on that device as degraded
- C. Waits for the configured delay timer before rebuild
- D. Marks all components on that device as stale
- E. Starts component rebuild immediately

Correct Answer: AC

Reference: <https://storagehub.vmware.com/t/vmware-vsan/vsan-6-7-proof-of-concept-guide/disk-failures-9/>

QUESTION 3

A storage policy has these rules:

Site disaster tolerance: None - standard cluster

Failures To Tolerance: 2 failures - RAID-1 (Mirroring)



What is the minimum number of hosts required to comply with this storage policy?

- A. 3
- B. 4
- C. 5
- D. 6

Correct Answer: A

Reference: <https://docs.vmware.com/en/VMware-Cloud-on-AWS/services/com.vmware.vsphere.vmc-aws-manage-data-center.doc/GUID-EDBB551B-51B0-421B-9C44-6ECB66ED660B.html>

QUESTION 4

End-users are complaining that an application running on an all-flash vSAN datastore is not performing well.

Which performance chart should an administrator view to troubleshoot this issue?

- A. Recovery Write IOPS
- B. Resync Latency
- C. Read Cache Read IOPS
- D. Write Buffer Free Percentage

Correct Answer: C

Reference: <https://docs.vmware.com/en/VMware-vSphere/6.7/vsan-673-monitoring-troubleshootingguide.pdf>

QUESTION 5

How are components marked on a capacity device that is inaccessible?

- A. reduced availability
- B. active-stale
- C. degraded
- D. absent

Correct Answer: C

The vSAN components that reside on the magnetic disk or flash capacity device are marked as degraded. Reference: <https://docs.vmware.com/en/VMware-vSphere/6.5/com.vmware.vsphere.virtualsan.doc/GUID9A2DCE0B-CFA1-41C1-97CE-DA56A55426EA.html>



VCE & PDF

Pass4itSure.com

<https://www.pass4itsure.com/5v0-21-19.html>

2024 Latest pass4itsure 5V0-21.19 PDF and VCE dumps Download

[5V0-21.19 PDF Dumps](#)

[5V0-21.19 Study Guide](#)

[5V0-21.19 Exam Questions](#)