



# 5V0-21.20<sup>Q&As</sup>

VMware Certified Master Specialist (HCI 2020)

**Pass VMware 5V0-21.20 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/5v0-21-20.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by VMware  
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which three should be taken into consideration when configuring a Stretched Cluster? (Choose three.)

- A. bandwidth between sites
- B. geographical distance
- C. number of objects
- D. vSphere version
- E. latency between sites

Correct Answer: ABC

---

**QUESTION 2**

A higher level of resiliency has been requested for an existing vSAN Stretched Cluster. A key requirement will be the addition of a third site to protect against a potential double site failure of the two mirrored sites in the stretched cluster. What solution would meet the resiliency requirement?

- A. Replicate to the third site at the VM level using vSphere Replication.
- B. Configure vSAN Stretched Cluster with FTT=2 to replicate to the third site.
- C. Add the third site to the existing vSAN Stretched Cluster.
- D. Replicate to the third site at the vSAN datastore level using Site Recovery Manager.

Correct Answer: C

---

**QUESTION 3**

Which step can be avoided when replacing a capacity tier device on a controller with passthrough mode and support for hot-plug?

- A. Shut down the host.
- B. Add the new disk to the disk group.
- C. Remove the disk from the disk group.
- D. Replace the physical drive.

Correct Answer: D

Reference: <https://docs.vmware.com/en/VMware-vSphere/6.5/virtual-san-66-administration-guide.pdf> (31)

---

**QUESTION 4**

What are two factors to consider prior to placing a vSAN node into Maintenance Mode with full data migration? (Choose two.)

- A. vSAN node must be removed from the cluster.
- B. vSAN must be disabled from command line on the host.
- C. Number of fault domains required to satisfy storage policies.
- D. Sufficient vSAN free storage capacity must exist.
- E. VMs registered to the host must be powered off.

Correct Answer: BD

Reference: <https://docs.vmware.com/en/VMware-vSphere/6.7/com.vmware.vsphere.virtualsan.doc/GUID-521EA4BC-E411-47D4-899A-5E0264469866.html>

---

**QUESTION 5**

An infrastructure architect is designing a vSAN Cluster that must satisfy these requirements:

support storage policies with 2 failures ?RAID-1 (Mirroring)

support storage policies with 2 failures ?RAID-6 (Erasure Coding)

virtual machines must maintain compliance with the storage policy rules above when one host is in maintenance mode with full data migration

What is the minimum number of hosts needed to achieve these design requirements?

- A. 6
- B. 8
- C. 5
- D. 7

Correct Answer: A

Reference: <https://docs.vmware.com/en/VMware-Cloud-on-AWS/services/com.vmware.vsphere.vmc-aws-manage-data-center-vms.doc/GUID-EDBB551B-51B0-421B-9C44-6ECB66ED660B.html>

[Latest 5V0-21.20 Dumps](#)

[5V0-21.20 VCE Dumps](#)

[5V0-21.20 Study Guide](#)