



5V0-21.20^{Q&As}

VMware Certified Master Specialist (HCI 2020)

Pass VMware 5V0-21.20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/5v0-21-20.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by VMware
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

When designing a vSAN Cluster, which three should be considered when sizing a vSAN datastore? (Choose three.)

- A. Storage Policy or Policies to be used
- B. capacity device queue depth
- C. vSAN Slack Space
- D. cache disks with 10% of the Disk Group
- E. On-Disk Format overhead
- F. endurance level of capacity disk used

Correct Answer: ABC

Reference: <https://core.vmware.com/resource/vmware-vsan-design-guide>

QUESTION 2

Which storage policy can be assigned to virtual machines in a 5-node, all flash vSAN cluster, to provide the highest level of redundancy?

- A. 1 failure

Correct Answer: B

QUESTION 3

Which is true of the vSAN iSCSI target service?

- A. It is a VMware supported cost effective way to provide shared storage to another hypervisor.
- B. The vSAN default storage policy determines the characteristics of the vSAN iSCSI target service storage objects.
- C. Security is provided through the iSCSI CHAP and Mutual CHAP Authentication methods.
- D. It is a VMware supported solution to provide iSCSI targets to applications that require multiple connections per session (MCS).

Correct Answer: B

QUESTION 4



An administrator observes this health check warning:

Controller firmware is VMware certified

They proceed to update the latest firmware on the Storage Controller. After a successful firmware upgrade, the same health check alert continues to display.

Which statement is true?

- A. Controller is not VMware certified and hence any firmware version displays a warning.
- B. The recently installed firmware is yet to be certified and included in VMware Compatibility Guide.
- C. The VMware vSAN Health Service needs to be restarted for changes to take effect.
- D. The alert can be ignored and silenced, since the firmware is newer than the recommended firmware.

Correct Answer: B

Reference: <https://kb.vmware.com/s/article/2150398>

QUESTION 5

A major upgrade of the ESXi code on an existing vSAN cluster was just completed. Upon logging on to the vSphere Web Client, the vSphere administrator encounters UI timeouts on vSAN specific menus. What could cause this?

- A. vSphere Update Manager is offline.
- B. vSAN Performance Service is offline.
- C. vCenter Server has yet to be upgraded.
- D. vSAN on-disk format has yet to be upgraded.

Correct Answer: C

[5V0-21.20 PDF Dumps](#)

[5V0-21.20 Study Guide](#)

[5V0-21.20 Braindumps](#)