



# 642-241<sup>Q&As</sup>

Unified Contact Center Enterprise Design (UCCED)

## Pass Cisco 642-241 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/642-241.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Microsoft Windows Active Directory in Cisco Unified Contact Center Enterprise controls all of these types of user access except which one?

- A. Supervisor CTI OS or Cisco Agent Desktop user login
- B. ConfigManager user access on Admin Workstation
- C. WebView user login
- D. service account login

Correct Answer: A

---

**QUESTION 2**

When using the Cisco Unified Contact Center Enterprise 8.0(x) Multi-Line ACD feature, which configuration item is not supported in the Cisco Unified Communications Manager?

- A. Busy triggers on each line must be set to one.
- B. Maximum number of calls on each line must be set to two.
- C. Agent ACD line can be a shared line.
- D. Lines can be configured to forward calls to other lines on the phone.

Correct Answer: C

---

**QUESTION 3**

Which node in a Cisco Unified Contact Center Enterprise system should be used to modify contact center configuration?

- A. Cisco Unified Contact Center Enterprise Logger
- B. Cisco Unified Contact Center Enterprise Call Router
- C. Cisco Unified Contact Center Enterprise NIC
- D. Cisco Unified Contact Center Enterprise Administrative Server
- E. Cisco Unified Contact Center Enterprise Peripheral Gateway

Correct Answer: D

---

**QUESTION 4**



Which statement is correct about the Erlang-C sizing calculation model?

- A. Erlang-C assumes that calls that do not find an available agent will be blocked or dropped.
- B. Erlang-C plans for a percentage of calls to be blocked or dropped in the calculation.
- C. Erlang-C is used for sizing IVR, PSTN trunk, and queue ports.
- D. Erlang-C is used for sizing agents in a queuing model.

Correct Answer: D

---

#### QUESTION 5

In a single-site deployment model for Cisco Unified Contact Center Enterprise, which statement is true?

- A. The Cisco Unified Communications Manager cluster can be split between two data center locations.
- B. The Cisco Unified Contact Center Enterprise agents are colocated at the same site as the data center components.
- C. The Cisco Voice Gateways can be distributed at multiple locations.
- D. The Cisco Unified IP IVR must be deployed with the G.279 codec for local voice quality.

Correct Answer: B

[Latest 642-241 Dumps](#)

[642-241 PDF Dumps](#)

[642-241 Practice Test](#)