

642-437^{Q&As}

Implementing Cisco Unified Communications Voice over IP and QoS v8.0 (CVOICE v8.0)

Pass Cisco 642-437 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/642-437.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers



VCE & PDF Pass4itSure.com

https://www.pass4itsure.com/642-437.html

2022 Latest pass4itsure 642-437 PDF and VCE dumps Download

QUESTION 1

Your PSTN carrier sends digits to your T1 PRI circuit in a digit-by-digit format. How must the T1 PRI circuit be configured to support this capability?

- A. The T1 PRI controller supports either en-bloc or digit-by-digit formats natively.
- B. The serial interface that is associated with the T1 controller needs to include the isdn incoming-voice command.
- C. The T1 controller needs to include the isdn overlap-receiving command.
- D. The serial interface that is associated with the T1/E1 controller needs to include the isdn overlap-receiving command.

Correct Answer: D

Explanation: Configuring Overlap-receiving on the D-channel changes the way routers behave when receiving ISDN calls. Overlap receiving allows the matching of dial peers as the digits are being received. The router responds to the setup message with a SETUP ACK. This informs the network that it is ready to receive further information messages containing additional call routing elements. http://www.cisco.com/en/US/tech/tk801/tk133/technologies_tech_note09186a00800b48cb.shtml

QUESTION 2

When a LAN switch port is configured with mls qos trust cos, if the pass-through dscp command option isn\\'t present, how will the switch port treat incoming DSCP-marked frames?

- A. It will pass the DSCP-marked frames.
- B. It will re-mark the DSCP frames according to the CoS-to-DSCP mapping table.
- C. The port will re-mark the frames according to the DSCP-to-CoS mapping table.
- D. The switch port will convert the DSCP setting to CoS values and use that to select the egress queue for the frame.

Correct Answer: B

QUESTION 3

How many VoIP G.711 calls can be made simultaneously over a 256-kb/s Frame Relay circuit (Layer 3) if cRTP is enabled and the default IOS voice payload size of 160 is used?

- A. 1
- B. 3
- C. 4
- D. 5

Correct Answer: B

https://www.pass4itsure.com/642-437.html

2022 Latest pass4itsure 642-437 PDF and VCE dumps Download

QUESTION 4

What is the minimum	number of F	RSVP peers	that are	necessary	for a Cisco	Unified Border	Element to	provide Cal
Admission Control?								

- A. 0
- B. 1
- C. 2
- D. 3
- E. 4

Correct Answer: C

QUESTION 5

Which voice feature operates the same as a firewall on a data network?

- A. digit manipulation
- B. call coverage
- C. calling privileges
- D. call routing and path selection

Correct Answer: C

Latest 642-437 Dumps

642-437 Practice Test

642-437 Exam Questions



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.pass4itsure.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4itsure, All Rights Reserved.