642-732^{Q&As}

Conducting Cisco Unified Wireless Site Survey (CUWSS) v2.0

Pass Cisco 642-732 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/642-732.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Cisco Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

A company has requested an indoor wireless survey that supports 5GHz radio, 3x4 MIMO technology, and 3 spatial streams. Which AP is used to perform this survey?

A. 600

B. 1242

C. 1600

D. 2600

E. 3600

Correct Answer: D

QUESTION 2

A network engineer is conducting an active wireless survey. Which four actions must be performed to ensure a successful survey? (Choose four.)

A. Use the same AP model for the survey that is used in production.

B. Point the antenna of the survey laptop towards the access point.

C. Perform the survey when site is empty.

D. Place the survey laptop antenna on a pole while surveying.

E. Look for potential barriers of the propagation of RF signals.

F. Identify areas that have high user density.

G. Use the same wireless devices that the customer will use.

Correct Answer: AEFG

QUESTION 3

The wireless survey report shows APs staggered throughout a facility, with several of them placed right on the exterior walls. Other APs are located right at building corners and major turns in the structure layout. Assuming all survey locations are optimized with a minimum of -67 RSSI at cell edges with 20% overlapping cells, for what purpose can this survey model be used?

A. location based services and BYOD preparation

B. voice and data clients with video on demand

C. streaming video with VoIP and data as an option

D. location services, VoIP, data, and video

Correct Answer: D

QUESTION 4

On which two items will data be collected when an engineer is conducting a passive survey? (Choose two.)

A. RF interference

B. rate shifting data rates

C. roaming

D. rouges

E. encryption

Correct Answer: AD

QUESTION 5

An engineer notes that some areas of a floor fail when using the Location Readiness Tool in Cisco WCS. What criteria must be met for a point to be considered location ready?

A. one AP in each quadrant, with three less than 70 feet away

B. one AP in three quadrants, with two less than 70 feet away

C. one AP in each quadrant, with two less than 70 feet away

D. one AP in three quadrants, with one less than 70 feet away

Correct Answer: A

Latest 642-732 Dumps   642-732 Exam Questions   642-732 Braindumps

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

https://www.pass4itsure.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: