

642-980^{Q&As}

Troubleshooting Cisco Data Center Unified Fabric

Pass Cisco 642-980 Exam with 100% Guarantee

Free Download Real Questions & Answers PDF and VCE file from:

https://www.pass4itsure.com/642-980.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by Cisco
Official Exam Center

- Instant Download After Purchase
- 100% Money Back Guarantee
- 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Refer to the exhibit.


The customer informs you of aproblem they are encountering. What is the cause of the problem?

- A. The core upstream switch does not have NPIV enabled.
- B. The downstream switch does not have NPIV enabled.
- C. NPIV has been disabled on all switches.
- D. NPIV has been configured but not enabled on the uplink port.

Correct Answer: A

QUESTION 2

Refer to the exhibit.



During a VSAN outage, youcome across this configuration. Please select two possible causes? (Choose two)

VCE & PDF Pass4itSure.com

https://www.pass4itsure.com/642-980.html

2022 Latest pass4itsure 642-980 PDF and VCE dumps Download

- A. no common VSANs on both switches
- B. no common trunks
- C. no common VSAN members in the same trunk
- D. VSANs in trunk are the same, but the trunk is not up

Correct Answer: AC

QUESTION 3


Which configuration is needed to suppress duplicate IP addresses when HSRP localization is enabled?

- A. Configure matching passwords in each data center.
- B. Configure no ip arp gratuitous hsrp duplicate under the VLAN.
- C. Remove the passwords in each data center.
- D. Configure mismatching HSRP versions between data centers.
- E. Change one data center to run VRRP rather than HSRP.

Correct Answer: B

QUESTION 4

Refer to the exhibit.



An administrator is trying to configure a port channel on a Cisco Nexus 7000 Series Switch, which is connected to a Cisco Nexus 5500 Series Switch. The port channel will not come up, so theadministrator executes the show port-channel summary command on the Cisco Nexus 7000 SeriesSwitch and displays the output.

What are two causes of the error? (Choose two.)

- A. The Cisco Nexus 7000 Series Switch needs to be configured with no lacp suspend- individual.
- B. The Cisco Nexus 5500 Series Switch is configured with channel-group mode on.



https://www.pass4itsure.com/642-980.html

2022 Latest pass4itsure 642-980 PDF and VCE dumps Download

- C. The LACP feature has not been enabled on the Cisco Nexus 7000 Series Switch.
- D. The ports are cabled to the wrong switch.
- E. The port channel load-balancing algorithm does not match.

Correct Answer: BD

QUESTION 5

nstructions




- Enter NX-OS commands on the device to verify network operation and answer the multiple-choice questions.
- THIS TASK DOES NOT REQUIRE DEVICE CONFIGURATION.
- · Click on the Console PC to gain access to the console of the router. No console or enable passwords are required.
- To access the multiple-choice questions, click on the numbered boxes on the left of the top panel.
- There are four multiple-choice questions with this task. Be sure to answer all four questions before clicking the Next button.

Scenario





The following four questions cover the Cisco Nexus 7010 and Nexus 5000 switches, which are at the core of a data center network. Utilize all the available **show** commands to answer the items. Access to the running configuration is not allowed.





https://www.pass4itsure.com/642-980.html 2022 Latest pass4itsure 642-980 PDF and VCE dumps Download









https://www.pass4itsure.com/642-980.html

2022 Latest pass4itsure 642-980 PDF and VCE dumps Download

Cisco UCS users residing behind N5K2 are complaining about poor performance with a single LAN application in the data center. Which statement best explains what is wrong with N5K2?

- A. Traffic balancing is based on the destination IP address.
- B. Port channel members do not have equal bandwidths.
- C. The trunk between the Nexus 5000 switches is filtering all VLANs.
- D. E2/1 on N7010-C2 is not configured as a trunk for application traffic from N5K2.

Correct Answer: A

Traffic balancing is based on the destination IP address Use the "show port-channel load-balance" command to verify.

Latest 642-980 Dumps

642-980 PDF Dumps

642-980 Exam Questions



To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product!

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications. You can view Vendor list of All Certification Exams offered:

https://www.pass4itsure.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:





Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © pass4itsure, All Rights Reserved.