



71200X^{Q&As}

Avaya Aura Core Components Integration Exam

Pass Avaya 71200X Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/71200x.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by Avaya
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

You need to enable the digit 8 to be used as the AAR access code. Which SAT command would you use to define the digit 8 as the AAR access code?

- A. change aar analysis
- B. change aar parameters
- C. add aar parameters
- D. change feature-access-code

Correct Answer: D

```
change feature-access-codes                                     Page 1 of 1
FEATURE ACCESS CODE (FAC)
Abbreviated Dialing List1 Access Code: 42
Abbreviated Dialing List2 Access Code: #80
Abbreviated Dialing List3 Access Code: 60
Abbreviated Dial - Prgm Group List Access Code: #99
Announcement Access Code: *99
Answer Back Access Code: #60
Attendant Access Code:
Auto Alternate Routing (AAR) Access Code: *00
Auto Route Selection (ARS) - Access Code 1: 9 Access Code 2: 813
```

QUESTION 2

Which statement about the Save translation command is true?

- A. It runs automatically after every SAT command.
- B. It writes a copy of the translation data to the FTP Server.
- C. It writes a copy of the translation data to the hard drive.
- D. It writes a copy of the translation data to RAM memory.

Correct Answer: C

QUESTION 3

In a survivable Aura core solution, for Avaya Aura Communication Manager (CM) Main Core to successfully send its translations to the Survivable Remote Server, the following actions must take place. Which three actions need to be performed to make this happen? (Choose three.)

- A. The File Synchronization Address(s) must be configured in SMI of the survivable server to point to Core CM.



- B. The survivable server and Core CM(s) must have same "Server ID".
- C. The survivable CM server must register with Processor Ethernet or CLAN of Main Core.
- D. The survivable server and Core CM must have different Module IDs (MID).

Correct Answer: ACD

QUESTION 4

AVAYA
Aura® System Manager 7.0

Last Logged on at February 24, 201... Log off

Home Routing

Home / Elements / Routing

Introduction to Network Routing Policy

Network Routing Policy consists of several routing applications like "Domains", "Locations", "SIP Entities", etc.

The recommended order to use the routing applications (that means the overall routing workflow) to configure your network configuration is as follows:

- Step 1: Create "Domains" of type SIP (other routing applications are referring domains of type SIP).
- Step 2: Create "Locations"
- Step 3: Create "Adaptations"
- Step 4: Create "SIP Entities"

- SIP Entities that are used as "Outbound Proxies" e.g. a certain "Gateway" or "SIP Trunk"
- Create all "other SIP Entities" (Session Manager, CM, SIP/PSTN Gateways, SIP Trunks)
- Assign the appropriate "Locations", "Adaptations" and "Outbound Proxies"

Call Admission Control (CAC) Sharing, introduced In Avaya Aura 7.1 allows which two components of Avaya Aura to centrally coordinate the allocation of bandwidth for calls? (Choose two.)

- A. System Manager
- B. Media Server
- C. Session Manager
- D. Communication Manager

Correct Answer: CD

QUESTION 5

Under which circumstance would an Avaya Aura Session Manager (SM) alarm be automatically cleared?

- A. After 24 hours of the alarm's first report occurrence
- B. When the alarm condition has been resolved
- C. If an automatic alarm clearing rule has been specified
- D. During the automatic nightly Avaya Aura System Manager (SMGR) alarm clearing



Correct Answer: B

[Latest 71200X Dumps](#)

[71200X Study Guide](#)

[71200X Braindumps](#)