



C1000-031^{Q&As}

IBM Power Systems Scale-Up Technical Sales

Pass IBM C1000-031 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/c1000-031.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers





QUESTION 1

A customer would like to have the ability to move cores and memory activations between servers inside a pool.

What kind of activation must be considered?

- A. Trial capacity on demand
- B. Mobile activation
- C. Elastic capacity on demand
- D. Static activation

Correct Answer: C

QUESTION 2

Which of the following statements is true regarding Power Enterprise Pools?

- A. The XML configuration file can be downloaded from the ESS (My Entitled Systems Support) web site.
- B. One Enterprise pool can contain the following machine types: Power Systems E870, E870C, E880C, and E980.
- C. Mobile activations can be moved within a pool at any time, without contacting IBM.
- D. A minimum of 75% of a system's memory activation can be mobile.

Correct Answer: C

Reference: <https://www-01.ibm.com/support/docview.wss?uid=nas8N1022430>

QUESTION 3

Which IBM Power Systems Software provides network firewall services with the local virtualized server to control network traffic between LPARs?

- A. PowerSC
- B. Trusted AIX
- C. PowerVC
- D. Trusted Surveyor

Correct Answer: A

Reference: http://www.common.be/system/files/files/Power_Systems_2013_PC.pdf (20)

**QUESTION 4**

What POWER9 processor capability has been enhanced, relative to POWER8, to enable more efficient processor utilization in support of some applications?

- A. SMT8 Fused Core Optimization
- B. SMT16 Simulation Mode
- C. Direct Attached Memory Mode
- D. AltiVec Instruction set

Correct Answer: D

QUESTION 5

A customer with a Power System 770 and direct SAN I/O is planning a migration to a Power System E980. The Power System 770 has four 8Gb PCIe 2-port full-height Fibre Channel adapters with all storage going through the SAN. The customer wants to keep the same WWPNs, and avoid a SAN reconfiguration.

What procedure should be recommended?

- A. Order new HBAs, but keep using the existing, already configured SAN switches.
- B. Order a PCIe Gen3 I/O Expansion Drawer and relocate the HBAs into the drawer.
- C. Order new HBAs and modify the WWPNs in the ASMI.
- D. Move the HBAs from the Power 770 and install them into the Power System E980 system node.

Correct Answer: D

[C1000-031 PDF Dumps](#)

[C1000-031 VCE Dumps](#)

[C1000-031 Exam Questions](#)