



C1000-031^{Q&As}

IBM Power Systems Scale-Up Technical Sales

Pass IBM C1000-031 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/c1000-031.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

Which of the following needs to be taken into consideration when designing an IBM Power System E980 solution?

- A. Each system node has eight PCI full-size Gen3 slots which are a mix of x8 and x16 PCIe slots.
- B. A DVD drive must be included in either the system control unit or in a system node.
- C. Redundant SAS controllers in each system node manage all six system node SAS bays.
- D. Only low profile PCIe adapters are supported in the system node.

Correct Answer: A

Reference: <https://www-01.ibm.com/common/ssi/cgi-bin/ssialias?infotype=ANandsubtype=CAandhtmlfid=877/ENUSZG18-0086andappname=lenovospainandlanguage=es>

QUESTION 2

Which IBM product is used to create, deploy, and manage virtual machines?

- A. PowerSC
- B. PowerVC
- C. PowerHA Enterprise Edition
- D. PowerVM Enterprise Edition

Correct Answer: B

QUESTION 3

A customer has a 40 core Power System E980 and would like to use Mobile Capacity on Demand.

What is the minimum of static processor activations that are required?

- A. 10
- B. 12
- C. 20
- D. 8

Correct Answer: D

Reference: <https://www-01.ibm.com/common/ssi/cgi-bin/ssialias?htmlfid=899/ENUSLG180083andinfotype=ANandsubtype=CA>



QUESTION 4

What are IBM's recommended best practices for racking and cabling on the IBM Power System E980?

- A. Use the eight inch rack rear expansion.
- B. Place the PDUs in the rack's vertical side pockets.
- C. Use the acoustic rack doors to minimize floor space and protect operator hearing.
- D. Locate the EXP24S SAS drawers in a different rack from the node of PCIe I/O drawer containing the SAS adapters running them.

Correct Answer: C

QUESTION 5

A customer has a mission-critical IBM i application running on a POWER9 processor-based server that requires eight processor licenses. For High Availability, a POWER9 CBU server is synchronized with the production server using PowerHA for IBM i.

What is the minimum number of IBM i processor licenses required on the CBU server?

- A. 2
- B. 4
- C. 1
- D. 8

Correct Answer: C

[C1000-031 PDF Dumps](#)

[C1000-031 VCE Dumps](#)

[C1000-031 Practice Test](#)