



C2090-317^{Q&As}

DB2 11 System Administrator for z/OS

Pass IBM C2090-317 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/c2090-317.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A member of a DB2 data sharing group (DB2A) has failed and is currently down. After a few minutes the phone starts ringing and people complain that transactions accessing table space TSA (in database DBA) get an SQLCODE -904 because of retained locks held by the member that just abended.

What is the recommended way to resolve this problem?

- A. -START DB(DBA) SP(TSA) ACCESS(FORCE)
- B. Restart the failed DB2 member with the LIGHT(YES) option.
- C. Delete all the failed persistent connections to the lock structure with the SETXCFFORCE,CONNECTION,STRNAME=lock_strname.CONNAME=ALL command and force the deallocation of the lock structure by issuing SETXCFFORCE,STRUCTURE.STRNAME=lock_strname
- D. Issue the MODIFY irlmproc.PURGE. DB2A command from an IRLM that is used by a DB2 member that is still running.}

Correct Answer: C

QUESTION 2

You wish to set the threshold at which data in the class castout queue is cast out to disk for group buffer pool GBP10. You want the threshold to be 1000 pages.

Which parameter setting in the command -ALTER GBPOOL(GBP10) will accomplish this?

- A. GBPOOLT(10)
- B. CLASST(0.1000)
- C. CLASST(10.1000)
- D. GBPCHKPT(1000)

Correct Answer: A

QUESTION 3

You want to temporarily switch-off one of your trusted contexts. How can this be accomplished?

- A. DROP TRUSTED CONTEXT...
- B. -STOP DB(DSNDB06) TS(SYSCONTX)
- C. ALTER TRUSTED CONTEXT ... DISABLE
- D. -STOP TRACE(AUDIT) AUDTPLCY(TRUSTED_CONTEXT)

Correct Answer: C



QUESTION 4

Given a subsystem parameter of SEPARATE_SECURITY=YES, what level of security has the authority to create and start audit policies?

- A. SYSOPR
- B. SYSADM
- C. SECADM
- D. SQLADM

Correct Answer: C

QUESTION 5

Which method can be used to set the DB2 client information (workstation name, application name..) from a JDBC application using a type 4 connection?

- A. Using the `java.sql.Connection.setClientInfo` method
- B. Using the SET_CLIENT_ID option during RRS SIGNON
- C. Using the SQL SET statement (eg. SET CURRENT CLIENT J/VRKSTNNAME = \\MYWS*)
- D. Setting up a profile using the SPECIAL_REGISTER attribute in SYSIBM.DSN PROFILE ATTRIBUTES table

Correct Answer: C

[C2090-317 Practice Test](#)

[C2090-317 Study Guide](#)

[C2090-317 Braindumps](#)