



C9010-022^{Q&As}

IBM AIX Administration V1

Pass IBM C9010-022 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/c9010-022.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

A customer has been creating LPARs on a new POWER8 system.

After successfully activating the first 10 LPARs, the customer notices that the available RAM on physical machine reported by the HMC has reduced more than the sum of the memory currently allocated to the activated LPARs.

The Customer appreciates there will be a memory overhead for each activated LPAR, but the overhead appears more than expected.

Which LPAR attribute is the likely cause for the excess in memory consumption?

- A. Active memory expansion factor
- B. Maximum Virtual Adapters
- C. Maximum memory
- D. Maximum pages

Correct Answer: A

QUESTION 2

What can be used to initiate patching of AIX LPARs, HMCs and VIO Server?

- A. IBM Systems Director (ISD)
- B. Network Install Manager (NIM)
- C. Electronic Service Agent (ESA)
- D. Service Update Management Assistant (SUMA)

Correct Answer: A

QUESTION 3

A company has combined multiple Web servers into one AIX LPAR with a single physical network connection. How can AIX be configured with multiple IP addresses on the same physical connection?

- A. Add the additional IP addresses as aliases in DNS.
- B. Add the IP addresses to the primary hostname line in /etc/hosts.
- C. Add the additional IP addresses as aliases to the network connection.
- D. Assign the IP addresses to virtual Ethernet adapters and map them to the physical network connection.

Correct Answer: C



QUESTION 4

Which action will temporarily disable remote login access using telnet and ssh for all non- root accounts?

- A. Update /etc/security/passwd and recycle the inetd subsystem.
- B. Stop the sshd subsystem.
- C. Create a/etc/nologin file.
- D. Set the PermitLogins parameter in /etc/ssh/sshd_config and recycle the sshd daemon.
- E. Touch the /etc/sshd/nologin file and recycle the sshd daemon.

Correct Answer: C

QUESTION 5

A system that will be re-installed has the following characteristics:

```
$ lspv
hdisk0          00c9d4cf1c892c4c          rootvg          active
hdisk1          0006bf1c3d81743b          None
hdisk2          0006bf1c3d817913          None
hdisk3          0006bf1c3e20e9f5          None
```

If the following target_disk_data stanza is defined in the bosinst.data file used for the install, which disk will be installed with the operating system?

target_disk_data:

LOCATION = 0006bf1c3d817913

SIZE_MB =

HDISKNAME = hdisk1

- A. hdisk0
- B. hdisk1
- C. hdisk2
- D. hdisk3

Correct Answer: C