



# C9530-410<sup>Q&As</sup>

IBM MQ V8.0 System Administration

**Pass IBM C9530-410 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/c9530-410.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by IBM Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

On a Linux system, a system administrator needs to change the default queue manager from QM1 to a newly created queue manager QM2.

How can the system administrator do this?

- A. Re-create QM2 with the -doption.
- B. Use the ALTER QMGR command.
- C. Edit the DefaultQueueManager stanza in qm.ini replacing QM1 with QM2.
- D. Change the queue manager name on the Name attribute of the DefaultQueueManager stanza to QM2 in mqsd.ini.

Correct Answer: D

---

**QUESTION 2**

The security exit code for a RECEIVER channel has been modified. What does the system administrator have to do to activate the changed security exit with minimum impact to the running systems?

- A. Stop and restart the queue manager.
- B. Stop and restart the channel from the SENDER side.
- C. Issue command REFRESH SECURITY TYPE EXIT.
- D. Issue command ALTER CHANNEL SCYEXIT SCYDATA \\REFRESH\\

Correct Answer: D

---

**QUESTION 3**

A system administrator of a z/OS queue manager expects to have 1000 client channels connecting with the queue manager at the same time.

What should system administrator do to tune the channel initiator to handle this work?

- A. Use the default values for the channel initiator parameters.
- B. Increase MAXCHL, ACTCHL, TCPCHL, CHIADAPS, and CHDISPS from the default values.
- C. Increase CHIADAPS and use the default values for CHDISPS, MAXCHL, ACTCHL, TCPCHL.
- D. Increase CHIADAPS and CHDISPS and use the default values for MAXCHL, ACTCHL, TCPCHL.

Correct Answer: B

---

**QUESTION 4**

A system administrator needs to ensure that MQ activity messages are created for an application message as it is routed through MQ network. What must the system administrator verify? choose 3

- A. The application has PUT authority to the activity message queues.
- B. The application message specifies that activity reports are to be generated.
- C. The MCA channels have been restarted after the configuration changes were made.
- D. Activity recording is enabled on every queue manager in the network.
- E. MQI statistics monitoring is enabled on every queue manager in the network.
- F. Queue manager events are enabled for every queue manager in the network.

Correct Answer: BCE

---

**QUESTION 5**

A client application receives an error MQRC Q FULL indicating that the queue is full. The administrator sets the queue properties for queue depth max events QDPMAXEV to ENABLED. Which setting must the system administrator configure at the queue manager level and which queue does the system administrator need to monitor for event messages?

- A. Inhibit Events set to Enabled Monitor the SYSTEM.ADMIN.INHIBIT.EVENT queue
- B. Remote Events set to Enabled Monitor the SYSTEM.ADMIN.QMGR.EVENT queue
- C. Performance Events set to Enabled Monitor the SYSTEM.ADMIN.PERFM.EVENT queue
- D. Configuration Events set to Enabled Monitor the SYSTEM.DEFAULT.MODEL.QUEUE queue

Correct Answer: C

[C9530-410 PDF Dumps](#)

[C9530-410 Study Guide](#)

[C9530-410 Braindumps](#)