



C_SECAUTH_20^{Q&As}

SAP Certified Technology Associate - SAP System Security and Authorizations

Pass SAP C_SECAUTH_20 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/c_secauth_20.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by SAP Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers





QUESTION 1

How can you enforce an additional transaction start authorization check for a custom transaction?

- A. Maintain the SU24 entry for the custom transaction and adding the desired authorization object, setting the Check Indicator to "Check" and setting Proposal to Yes.
- B. Using transaction SE93, update the custom transaction definition by specifying the desired authorization object and maintaining the desired field values.
- C. Without additional custom development it is not possible to add another check during transaction start.
- D. For each role containing the custom transaction, add the desired authorization object manually in transaction PFCG, maintain the field values and then generate the profile.

Correct Answer: A

QUESTION 2

Which of the following user types are precluded from logging onto the system directly? (Choose three.)

- A. Dialog
- B. Service
- C. Communication
- D. Reference
- E. System

Correct Answer: CDE

QUESTION 3

Which of the following are examples of personal data under the GDPR? (Choose three.)

- A. IP address
- B. Aggregated statistics on the use of a product
- C. GPS data from a cellular phone
- D. Age group
- E. E-mail address

Correct Answer: ACE



QUESTION 4

In the case of missing OData authorizations, why is it not recommended to maintain S_SERVICE manually within an SAP Fiori authorization role? (Choose two.)

- A. Both front-end and back-end entries are generating the same S_SERVICE authorization object with different authorization values.
- B. Both front-end and back-end entries are generating the same S_SERVICE authorization object with the same authorization values.
- C. The SRV_NAME value of the S_SERVICE authorization object is the name of an OData service.
- D. The SRV_NAME value of the S_SERVICE authorization object is the hash value of an OData service.

Correct Answer: AD

QUESTION 5

Which of the following are prerequisites for using transaction PFCG? (Choose two.)

- A. Maintain parameter auth/no_check_in_some_cases = Y
- B. Fill in initials values for customer tables using transaction SU25
- C. Maintain the Check Indicators for Critical Authorization objects
- D. Generate Standard Role SAP_NEW using transaction SU25

Correct Answer: AB

[C_SECAUTH_20 PDF Dumps](#)

[C_SECAUTH_20 Study Guide](#)

[C_SECAUTH_20 Exam Questions](#)