



CWAP-403^{Q&As}

Certified Wireless Analysis Professional

Pass CWNP CWAP-403 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/cwap-403.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

802.11k Neighbor Requests and Neighbor Reports are sent in what type of Management Frames?

- A. RRM
- B. Action
- C. Beacon
- D. Reassociation Request and Reassociation Response

Correct Answer: C

QUESTION 2

A manufacturing facility has installed a new automation system which incorporates an 802.11 wireless network. The automation system is controlled from tablet computers connected via the WLAN. However, the automation system has not gone live due to problem with the tablets connecting to the WLAN. The WLAN vendor has been onsite to perform a survey and confirmed good primary and secondary coverage across the facility. As a CWAP you are called in to perform Spectrum Analysis to identify any interference sources. From the spectrum analysis, you did not identify any interference sources but were able to correctly identify the issue. Which of the following issues did you identify from the spectrum analysis?

- A. The tablets are entering power save mode and failing to wake up to receive the access points transmissions
- B. A high noise floor has resulted in a SNR of less than 20%
- C. The tablets are connecting to the wrong SSID
- D. There is a power mismatch between the APs and the clients

Correct Answer: A

QUESTION 3

Given: The Frame Check Sequence (FCS) is a 32 CRC used for error detection. The CRC is calculated over what?

- A. Frame Body only
- B. Mac Header and Frame Body only
- C. PHY Header, MAC Header and Frame Body
- D. PHY Header and MAC Header only

Correct Answer: B

QUESTION 4



What is the formula used to calculate the Duration field value in an RTS frame?

- A. RTS Duration field = CTS duration
- B. RTS Duration field = Data or management to be sent frame duration
- C. RTS Duration field = Data or management frame to be sent duration + CTS duration + one ACK duration + three SIFS
- D. RTS Duration field = Data or management frame to be sent duration + CTS duration

Correct Answer: C

QUESTION 5

What is the default 802.11 authentication method for a STA when using Pre-RSNA?

- A. Open System
- B. Shared Key
- C. 4-Way Handshake
- D. PSK

Correct Answer: A

[CWAP-403 PDF Dumps](#)

[CWAP-403 Practice Test](#)

[CWAP-403 Study Guide](#)