



CWAP-403^{Q&As}

Certified Wireless Analysis Professional

Pass CWNP CWAP-403 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/cwap-403.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

Protocol analyzers may present field values in either binary, decimal or hexadecimal. What precedes a hexadecimal value to indicate it is hexadecimal?

- A. 0x
- B. %
- C. HEX
- D. 16x

Correct Answer: A

QUESTION 2

As a wireless network consultant you have been called in to troubleshoot a high-priority issue for one of your customers. The customer's office is based on two floors within a multi-tenant office block. On one of these floors (floor 5) users cannot connect to the wireless network. During their own testing the customer has discovered that users can connect on floor 6 but not when they move to the floor 5. This issue is affecting all users on floor 5 and having a negative effect on productivity. To troubleshoot this issue, you perform both Spectrum and Protocol Analysis. The Spectrum Analysis shows the presence of Bluetooth signals which you have identified as coming from wireless mice. In the protocol analyzer you see the top frame on the network is deauthentication frames. On closer investigation you see that the deauthentication frames' source addresses match the BSSIDs of your customers APs and the destination address is FF:FF:FF:FF:FF:FF:FF:FF. What do you conclude from this troubleshooting exercise?

- A. The customer should replace all their Bluetooth wireless mice as they are stopping the users on floor 5 from connecting to the wireless network
- B. The users on floor 5 are being subjected to a denial of service attack, as this is happening across the entire floor it is likely to be a misconfigured WIPS solution belonging to the tenants on the floor below
- C. The customers APs are misbehaving and a technical support case should be open with the vendor
- D. The CCI from the APs on the floor 4 is the problem and you need to ask the tenant below to turn down their AP's Tx power

Correct Answer: A

QUESTION 3

An RST frame should be acknowledged by which frame?

- A. Ack
- B. CTS
- C. Block Ack
- D. RTS-Ack



Correct Answer: A

QUESTION 4

Where would you look in a packet trace file to identify the configured Minimum Basic Rate (MBR) of a BSS?

- A. Supported Rates and Extended Supported Rates elements in a Beacon frame
- B. In the MBR Action frame
- C. In the Minimum Basic Rate Element in a Beacon frame
- D. In the MBR Information Element in an Association Response frame

Correct Answer: A

QUESTION 5

How many frames make up the Group Key Handshake excluding any Ack frames that may be required?

- A. 1
- B. 2
- C. 3
- D. 4

Correct Answer: D

[Latest CWAP-403 Dumps](#)

[CWAP-403 VCE Dumps](#)

[CWAP-403 Braindumps](#)