



# CWAP-403<sup>Q&As</sup>

Certified Wireless Analysis Professional

**Pass CWNP CWAP-403 Exam with 100% Guarantee**

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/cwap-403.html>

100% Passing Guarantee  
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP  
Official Exam Center

- ⚙️ **Instant Download** After Purchase
- ⚙️ **100% Money Back** Guarantee
- ⚙️ **365 Days** Free Update
- ⚙️ **800,000+** Satisfied Customers



**QUESTION 1**

The PLCP sublayer provides framing by adding a header to create what type of data unit?

- A. MSDU
- B. MPDU
- C. PSDU
- D. PPDU

Correct Answer: D

---

**QUESTION 2**

When a data frame is encrypted with WPA2, to which portion of the frame is the encryption applied?

- A. Frame body excluding the LLC
- B. Frame body including the LLC
- C. Frame body and MAC Header
- D. The whole MPDU

Correct Answer: C

---

**QUESTION 3**

Using a portable analyzer you perform a packet capture next to a client STA and you can see that the STA is associated to a BSS. You observe the STA sending packets to the AP and the AP sending packets to the STA. Less the 2% of all packets are retransmissions. You move to capture packets by the AP and, while the retry rate is still very low, you now only see unidirectional traffic from the AP to the client. How do you explain this behavior?

- A. There is a transmit power mismatch between the client and the AP and while the client can hear the Aps traffic, the AP cannot hear the client.
- B. The portable analyzer has a lower receive sensitivity than the AP and while it can't capture the packets from the client STA, the AP can receive them OK.
- C. The STA is transmitting data using more spatial streams than the portable analyzer can support
- D. The portable analyzer is too close to the AP causing CCI, blinding the AP to the client's packets

Correct Answer: B

---

**QUESTION 4**



What is the difference between a Data frame and a QoS-Data frame?

- A. QoS Data frames include a QoS control field
- B. QoS Data frames include a QoS information element
- C. QoS Data frames include a DSCP control field
- D. QoS Data frames include an 802.1Q VLAN tag

Correct Answer: A

---

#### QUESTION 5

A manufacturing facility has installed a new automation system which incorporates an 802.11 wireless network. The automation system is controlled from tablet computers connected via the WLAN. However, the automation system has not gone live due to problem with the tablets connecting to the WLAN. The WLAN vendor has been onsite to perform a survey and confirmed good primary and secondary coverage across the facility. As a CWAP you are called in to perform Spectrum Analysis to identify any interference sources. From the spectrum analysis, you did not identify any interference sources but were able to correctly identify the issue. Which of the following issues did you identify from the spectrum analysis?

- A. The tablets are entering power save mode and failing to wake up to receive the access points transmissions
- B. A high noise floor has resulted in a SNR of less than 20%
- C. The tablets are connecting to the wrong SSID
- D. There is a power mismatch between the APs and the clients

Correct Answer: A

[CWAP-403 PDF Dumps](#)

[CWAP-403 VCE Dumps](#)

[CWAP-403 Braindumps](#)