CWDP-302^{Q&As}

Certified Wireless Design Professional

Pass CWNP CWDP-302 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/cwdp-302.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

⚙ **Instant Download** After Purchase

⚙ **100% Money Back** Guarantee

⚙ **365 Days** Free Update

⚙ **800,000+** Satisfied Customers

QUESTION 1

You deployed an AP and installed its antenna, and you now need to set the AP transmit power. Given a desired EIRP of 21 dBm, and an antenna gain of 5.85 dBd connected through 25 feet of cable with a lossspecification of 4 dB/100 feet.

Assuming that there is no significant loss from the connectors, what should be the transmit power level for this AP?

A. 10 mW

B. 14 mW

C. 20 mW

D. 25 mW

Correct Answer: D

QUESTION 2

You desire to achieve a 450 Mbps MCS. What 802.11n features (from the numbered list below) are required?

1.

Frame aggregation

2.

Short GI

3.

40 MHz channels

4.

2 spatial streams

5.

3 spatial streams

6.

Transmit beamforming (TxBF)

A. 2,3,2

B. 1, 2, 3, 5

C. 1, 2, 3, 4, 6

D. 2,3,5

Correct Answer: D

QUESTION 3

You are testing a VoWLAN deployment, and your communication measurements show a certain amount of lost packets. What would be an acceptable packet error rate value to still provide acceptable call quality?

A. There should be 0% error in a VoWLAN type of deployment

B. No more than 1% PER max should be acceptable

C. No more than 4% PER max should be acceptable

D. No more than 8% PER max should be acceptable

Correct Answer: B

QUESTION 4

In a large enterprise (5000+ wireless users), by what would NOT be a recommended method by which IP addresses and VLANs are assigned to different clients associated to the same AP?

A. Each SSID is mapped to a static VLAN assignment

B. Upstream AAA servers dynamically assign VLANs to each user or group profile

C. Radio signal metrics (RSSI, SNR, etc.) of WLAN clients are triangulated for location- based VLAN assignment during association

D. Multiple VLAN pools are designated for an SSID and user IP addresses are selected in a round-robin fashion from the associated pools

Correct Answer: C

QUESTION 5

When performing an indoor predictive site survey to make the WLAN planning and design cycle more efficient, what is a best practice for configuration of the simulated APs in the predictive modeling software?

A. All simulated APs should be set to 20 MHz channels only.

B. Always use the default 2.2 dBi omnidirectional antenna patterns for simulated APs.

C. If dynamic RRM will be used, AP transmit power should be set to an estimated average level of the expected client devices, such as 25 mW.

D. Defining custom AP and antenna patterns will yield more accurate prediction data than the pre-configuredvendor AP/antenna combinations.

Correct Answer: C

Latest CWDP-302 Dumps   **CWDP-302 VCE Dumps**   **CWDP-302 Practice Test**

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Try our product !

100% Guaranteed Success
100% Money Back Guarantee
365 Days Free Update
Instant Download After Purchase
24x7 Customer Support
Average 99.9% Success Rate
More than 800,000 Satisfied Customers Worldwide
Multi-Platform capabilities - Windows, Mac, Android, iPhone, iPod, iPad, Kindle

We provide exam PDF and VCE of Cisco, Microsoft, IBM, CompTIA, Oracle and other IT Certifications.
You can view Vendor list of All Certification Exams offered:

https://www.pass4itsure.com/allproducts

Need Help

Please provide as much detail as possible so we can best assist you.
To update a previously submitted ticket: