

CWDP-303^{Q&As}

Certified Wireless Design Professional

Pass CWNP CWDP-303 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/cwdp-303.html

100% Passing Guarantee 100% Money Back Assurance

Following Questions and Answers are all new published by CWNP Official Exam Center

Instant Download After Purchase

- 100% Money Back Guarantee
- 😳 365 Days Free Update
- 800,000+ Satisfied Customers





QUESTION 1

Switches and APs have already been chosen by your customer. All switches support 802.3bz MultiGig interfaces and APs are 4x4:4 802.11ac wave 2 capable of using dual-5GHz and have one MultiGig interface. Some cable drops for the APs will run for more than 180.5 feet (or 55 meters). To support MultiGig, what is the best choice of cabling?

A. Cat-5

- B. Cat-6
- C. Cat-5e
- D. Cat-6a

Correct Answer: C

QUESTION 2

A controller-based WLAN infrastructure has its controller on a different subnet than its APs. What device

must be used to enable any communication between the Controller and the APs?

- A. NTP server
- B. Router
- C. PoE Layer 2 switch
- D. Wireless bridge
- Correct Answer: B

Reference: https://www.speaknetworks.com/cisco-wireless-controller-configuration/

QUESTION 3

What are the deliverables to your customer after successfully implementing a WLAN infrastructure?

- A. Digital or physical assets, guides, floorplans and configuration documents
- B. Project Charter
- C. Facility blueprints
- D. Nothing is required. The implemented WLAN was deliverable

Correct Answer: A

QUESTION 4



During a validation site survey, you realize that the installers mounted some of the APs above the ceiling. They said that this was a request from the building architect due to aesthetics constraints. During the requirements gathering, you weren\\'t advised about any aesthetics constraints from the main stakeholder of the project. What should you do in this case?

A. Advise the stakeholder that WLAN performance requirements will not be met and a new design process will be needed to meet the requirements.

- B. Leave it as it is and allow automatic channel management to correct any issues.
- C. Increase the output power on all APs by 6 dB immediately.
- D. Remove all external antennas and use only the internal antennas to reduce multipath.

Correct Answer: A

QUESTION 5

What is the most cost-effective way to accurately measure the height of a ceiling when ladder use is not allowed?

- A. Estimate the height based on known object sizes
- B. Gather measurements from other objects and do the math
- C. Rent a lift-cart to lift you up to the ceiling
- D. Use a laser measure to measure the distance from the floor to the ceiling

Correct Answer: D

CWDP-303 Practice Test CWDP-303 Exam Questions CWDP-303 Braindumps