CWNA-107^{Q&As}

CWNA-107^{Q&As}

Certified Wireless Network Administrator

Pass CWNP CWNA-107 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

https://www.pass4itsure.com/cwna-107.html

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

Instant Download After Purchase

100% Money Back Guarantee

365 Days Free Update

800,000+ Satisfied Customers

QUESTION 1

You are attempting to explain RF shadow and how it can cause lack of coverage. What common building item frequently causes RF shadow and must be accounted for in coverage plans?

A. Wooden doors

B. Carpeted floors

C. Elevators

D. Cubicle partitions

Correct Answer: D

QUESTION 2

Option 43 must be configured to allow access points to locate controllers. In what network service should this option be configured?

A. DHCP

B. LDAP

C. DNS

D. RADIUS

Correct Answer: A

Reference https://www.cisco.com/c/en/us/support/docs/wireless-mobility/wireless-lan-wlan/97066-dhcp-option-4300.html

QUESTION 3

You have received a report of poor wireless connections on the third floor of a building under your administration. Three individuals have reported the problem. Apparently, the connections are reposting a strong signal, but the users cannot access the Internet. With the problem identified, what is the next logical step in the troubleshooting process?

A. Perform corrective actions

B. Discover the scale of the problem

C. Create a plan of action or escalate the problem

D. Verify the solution

Correct Answer: A

QUESTION 4

You are deploying a WLAN monitoring solution that utilizes distributed sensor devices. Where should sensors be deployed for best results? Choose the single best answer.

A. Every 20 feet and alongside each AP

B. Closer to the APs

C. Closer to the client devices

D. IN critical areas where WLAN performance must be high

Correct Answer: C

QUESTION 5

You are troubleshooting a controller-based AP that is unable to locate the controller. DHCP is not used and the controller is located at 10.10.10.81/24 while the AP is on the 10.10.16.0/24 network. What should be inspected to verify proper configuration?

A. NTP

B. BOOTH

C. DNS

D. AP hosts file

Correct Answer: C

CWNA-107 Practice Test   CWNA-107 Study Guide   CWNA-107 Exam Questions