



CWNA-108^{Q&As}

Certified Wireless Network Administrator

Pass CWNP CWNA-108 Exam with 100% Guarantee

Free Download Real Questions & Answers **PDF** and **VCE** file from:

<https://www.pass4itsure.com/cwna-108.html>

100% Passing Guarantee
100% Money Back Assurance

Following Questions and Answers are all new published by CWNP
Official Exam Center

-  **Instant Download** After Purchase
-  **100% Money Back** Guarantee
-  **365 Days** Free Update
-  **800,000+** Satisfied Customers



**QUESTION 1**

You are configuring an access point to use channel 128. What important fact should be considered about this channel?

- A. It is a 22 MHz channel so it will overlap with the channels above and below it
- B. It is a 2.4 GHz frequency band 40 MHz channel, so it should not be used
- C. It is a channel that is unsupported by most access points
- D. It is a channel that likely requires DFS when used

Correct Answer: D

QUESTION 2

Three access points are used within a facility. One access point is on channel 11 and the other two are on channel 1. The two access points using channel 1 are on either side of the access point using channel 11 and sufficiently apart so that they do not interfere each other when they transmit frames. Assuming no other Aps are in the vicinity, is CCI still a possibility in this network and why?

- A. Yes, because the client devices connected to one of the channel 1 APs will transmit frames that reach the other channel 1 AP as well as
- B. No, because the Aps are far enough apart that no CCI will occur
- C. No, because CCI only occurs in the 5 GHz frequency band
- D. Yes, because channel 11 loops around and causes CCI with channel 1

Correct Answer: A

QUESTION 3

You are managing a wireless access point in autonomous mode using the Web based interface. You capture traffic during this management task and notice that you can see the HTML code of the Web pages for access point management. What error in administration could be the cause of the security concern?

- A. A VPN with the AP is not established
- B. WPA2 is disabled on the WLAN
- C. HTTP is in use instead of HTTPS
- D. IPsec is not in use of the management connection as recommended

Correct Answer: C

QUESTION 4



What ID is typically mapped to an AP's MAC address if a single BSS is implemented?

- A. SSID
- B. Device ID
- C. VLAN ID
- D. BSSID

Correct Answer: D

QUESTION 5

What is always required to establish a high quality 2.4 GHz RF link at a distance of 3 miles (5 kilometers)?

- A. Grid antennas at each endpoint
- B. A Fresnel Zone that is at least 60% clear of obstructions
- C. A minimum antenna gain of 11 dBi at both endpoints
- D. Minimum output power level of 2 watts

Correct Answer: B

[Latest CWNA-108 Dumps](#)

[CWNA-108 Study Guide](#)

[CWNA-108 Exam Questions](#)